

## **DECOSTAR 51 ECO 35 W 12 V 10° GU5.3**

DECOSTAR 51 ECO | Halogen dichroic reflector lamps with 51 mm diameter



### Areas of application

- General illumination
- Kitchen lighting
- · Dining table lighting
- · Mirror lighting
- Workplace lighting
- Shops
- · Restaurants, hotels and similar prestigious applications

#### **Product benefits**

- · Brilliant ECO accent lighting
- Significantly lower CO<sub>2</sub> emissions
- Constant luminous intensity and constant color location throughout
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- · Contains no mercury

#### **Product features**

· Average life: 5,000 h

Dimmable

Color rendering index R<sub>a</sub>: 100
Color temperature: 3,000 K





### Technical data

### Electrical data

Nominal wattage	35.00 W	
Nominal voltage	12 V	
Rated wattage	35.00 W	
Claimed equiv. conventional lamp power	50 W	
Power factor λ	1.00	
Energy consumption	38 kWh/1000h	


#### Photometrical data

Nominal useful luminous flux 90°	620 lm
Luminous intensity	11000 cd
Color temperature	3000 K
Light color as per EN 12464-1	Warm White
Color rendering index Ra	100
Lumen main.fact.at end of nom.life time	0.75
Rated useful luminous flux 90°	620 lm

## Light technical data

Beam angle	10 °
Starting time	0.0 s
Warm-up time (60 %)	0.00 s

## Dimensions & weight



### Product line drawing

<b>Diameter</b> 50.0 mm
-------------------------

Length	46.0 mm
Overall length	45.0 mm
Outer bulb	MR51
Maximum diameter	51.0 mm

#### Colors & materials


Lamp mercury content	0.0 mg
Mercury-free	Yes

### Lifespan

Nominal lamp life time	5000 h
Rated lamp life time	5000 h
Number of switching cycles	125000 <sup>1)</sup>

 $<sup>^{1)}</sup>$  At 1 min on / 3 min off

### Additional product data



### Spectral power distribution

Base (standard designation)	GU5.3
-----------------------------	-------

## Capabilities

Burning position	Any
Dimmable	Yes

#### **Certificates & standards**

Energy efficiency class	В
-------------------------	---

# **Country specific categorizations**

ILCOS	HRGS//UBIB-35-12-GU5.3-51/10	
Order reference	48865 ECO SP 35	

# Country specific information

Product code	METEL code	SEG number	STK number	UK Org
4050300516592	OSRH48865SPECO	8326920	4739656	-

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4050300516592	DECOSTAR 51 ECO 35 W 12 V 10° GU5.3	Folding carton box 1	46 mm x 46 mm x 58 mm	0.12 dm³	38.00 g
4050300533889	DECOSTAR 51 ECO 35 W 12 V 10° GU5.3	Shipping carton box 20	208 mm x 123 mm x 140 mm	3.58 dm <sup>3</sup>	836.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### References / Links

For light distribution curves see

www.osram.com

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.