

ST 172 SAFETY DEOS

Starters for series operation at 230 V AC $\,$



Product features

- Temperature range for reliable cut-out: -20...+80 °C




Product datasheet

Technical data

Electrical data

| Nominal voltage | 220240 V |
|-----------------|----------|
| Mains frequency | 5060 Hz |

Dimensions & weight



| Length | 40.3 mm |
|--------|---------|
| Length | 40.3 mm |

Lifespan

| Rated lamp life time | 0 h |
|----------------------|-----|
| • | |

Additional product data

| Lamp mercury content | 0.0 mg | | |
|-----------------------------------|--|--|--|
| Appropriate disposal acc. to WEEE | Yes | | |
| Footnote only for product | Temperature range for reliable switch-off: -20+80 °C | | |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (height x width x length) | Volume | Gross weight |
|---------------|-----------------------|---------------------------------|--------------------------------------|----------------------|--------------|
| 4050300797793 | ST 172 SAFETY DEOS | Shipping carton box 200 | 227 mm x 98 mm x 227 mm | 5.05 dm ³ | 2098.50 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.