

PRODUCT DATASHEET

HQI HIGHBAY 250 120° 95 W/4000K E40

HQI LED HIGHBAY | LED replacement for HID lamps for high-bay luminaires



AREAS OF APPLICATION

- LED alternative for applications requiring a high luminous flux
- Industrial and storage facilities
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Direct replacement for traditional HQI and NAV lamps thanks to CCG and ignitor compatibility
- Energy savings of up to 68 % when replacing traditional HQI lamps
- Effective thermal management for wide operating temperature range
- Low maintenance costs thanks to long lifetime
- Instant 100 % light, no warm-up time

PRODUCT FEATURES

- Type of protection: IP40
- High surge protection: up to 4 kV (L-N)



TECHNICAL DATA

Electrical data

Rated wattage	95.00 W
Nominal wattage	95.00 W
Nominal voltage	110 V
Max. lamp no. on circuit break. B10 A - CCG with compensation	6
Max. lamp no. on circuit break. B16 A - CCG with compensation	10
Operating frequency	50 Hz
Inrush current	≤75 A
Power factor λ	0.70


Photometrical data

Nominal luminous flux	13000 lm
Rated luminous flux	13000 lm
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Luminous flux	13000 lm
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdc _m
Rated color temperature	4000 K
Color rendering index Ra	≥80

Light technical data

Warm-up time (60 %)	< 0.50 s
Beam angle	120 °
Starting time	< 0.5 s

Dimensions & weight



Overall length	307.0 mm
Diameter	230.0 mm
Outer bulb	-
Length	307.0 mm

Temperatures & operating conditions

Ambient temperature range	-20...+50 °C
Maximum temperature at tc test point	65 °C

Lifespan

Nominal lamp life time	50000 h
Rated lamp life time	50000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

Additional product data

Base (standard designation)	E40
Mercury content	0.0 mg
Mercury-free	Yes
Show WEEE picto	Yes

Capabilities

Dimmable	No
-----------------	----

Certificates & standards

Energy efficiency class	A+
Energy consumption	95 kWh/1000h

Country-specific categorizations

Order reference	HQILEDH13000 95
------------------------	-----------------

EQUIPMENT / ACCESSORIES

- Safety sling for lamp included

SAFETY ADVICE

Not suitable for operation with 230 V line voltage.

The bulb may be larger and heavier than the replaced bulb. Before installation it must be checked, if the luminaire and especially the holder is capable of carrying the weight of the lamp.

Safety sling has to be installed.

To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

Only suitable for temperatures of up to 50°C inside of the luminaire.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075284722	Folding carton box 1	247 mm x 247 mm x 333 mm	1321.00 g	20.32 dm ³
4058075284739	Shipping carton box 4	515 mm x 515 mm x 355 mm	5961.00 g	94.15 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.