

## Parallel Connected Capacitors 250 V, 50/60 Hz

### Capacitors type A

Casing: plastics, white or aluminium

Fastening: male nipple


with nut and washer included

Discharge resistance

Optional: thermal cut-out,

European wide patent

On request with alternative capacities, connection terminals, mounting options, casing materials or with a thermal fuse as well as versions with IDC terminal for the automatic luminaire wiring



Ref. No.	Capacity µF	Temperature range °C	Ø (D) mm	Length (L) mm	Male nipple/ length (mm)	Push-in twin terminals	Weight g	Unit pcs.
<b>Plastic casing</b>								
500296	2.0	-40 to 85	30	53	M8x10	0.5-1 mm <sup>2</sup>	22	530
500299	2.5	-40 to 85	30	53	M8x10	0.5-1 mm <sup>2</sup>	22	530
500300	3.0	-40 to 85	25	57	M8x10	0.5-1 mm <sup>2</sup>	22	530
500301	3.5	-40 to 85	30	53	M8x10	0.5-1 mm <sup>2</sup>	22	530
500302	4.0	-40 to 85	30	53	M8x10	0.5-1 mm <sup>2</sup>	22	450
500303	4.5	-40 to 85	30	53	M8x10	0.5-1 mm <sup>2</sup>	22	450
500304	5.0	-40 to 85	30	53	M8x10	0.5-1 mm <sup>2</sup>	22	450
500305	6.0	-40 to 85	30	53	M8x10	0.5-1 mm <sup>2</sup>	22	450
506495	7.0	-40 to 85	30	53	M8x10	0.5-1 mm <sup>2</sup>	22	320
502783	8.0	-40 to 85	30	69	M8x10	0.5-1 mm <sup>2</sup>	24	320
504351	9.0	-40 to 85	30	69	M8x10	0.5-1 mm <sup>2</sup>	32	320
508667	10.0	-40 to 85	30	69	M8x10	0.5-1 mm <sup>2</sup>	32	320
506366	12.0	-40 to 85	30	78	M8x10	0.5-1 mm <sup>2</sup>	32	260
508468	15.0	-40 to 85	30	93	M8x10	0.5-1 mm <sup>2</sup>	36	260
508668	16.0	-40 to 85	30	93	M8x10	0.5-1 mm <sup>2</sup>	32	260
500315	18.0	-40 to 85	35	93	M8x10	0.5-1.5 mm <sup>2</sup>	36	190
500316	20.0	-40 to 85	35	93	M8x10	0.5-1.5 mm <sup>2</sup>	55	190
500317	25.0	-40 to 85	35	93	M8x10	0.5-1.5 mm <sup>2</sup>	66	80
500318	30.0	-40 to 85	40	93	M8x10	0.5-1.5 mm <sup>2</sup>	72	100
<b>Aluminium casing</b>								
500319	32.0	-40 to 85	35	135	M8x10	0.5-1.5 mm <sup>2</sup>	110	50
500320	35.0	-40 to 85	40	139	M8x10	0.5-1.5 mm <sup>2</sup>	127	36
500321	40.0	-40 to 85	40	139	M8x10	0.5-1.5 mm <sup>2</sup>	127	36
536406	45.0	-40 to 85	40	103	M8x10	0.5-1.5 mm <sup>2</sup>	120	36
500322	50.0	-40 to 85	45	103	M8x10	0.5-1.5 mm <sup>2</sup>	150	32
500323	55.0	-40 to 85	45	135	M8x10	0.5-1.5 mm <sup>2</sup>	159	32