

IP65 LED Floodlight



MLA part code	FLF10	FLF20	FLF30	FLF50	FLF80	FLF100
Description	LED floodlight					
Finishes	Black					
Net weight (kg)	0.426	0.675	0.888	1.698	3.698	3.693
Wattage (W)	10	20	30	50	80	100
Overall dimensions (mm)	Length: 130 Height: 90 Projection: 80	Length: 180 Height: 126 Projection: 87	Length: 210 Height: 147 Projection: 95	Length: 260 Height: 182 Projection: 106	Length: 360 Height: 254 Projection: 140	Length: 360 Height: 254 Projection: 140
Lumen Output (lm)	1150	2240	3100	5380	7740	8100
Efficacy (lm/W)	115	112	103	107	96	81
ErP Class	A++	A+	A+	A+	A+	A
Operating current (A)	0.079	0.118	0.148	0.233	0.351	0.468
P.F	>0.7	>0.8	>0.9	>0.9	>0.9	>0.9
CCT	4000K					
LED Colours	Cool white					
CRI	>70					
Input voltage	Mains 230V 50Hz					
Construction	Die cast Aluminium					
Class	Class I					
IP rating	IP65					
Life span	30,000 hrs					
Pre Wired	Yes with 1m cable					
Warranty	3 Years					
Dimmable	No					
Origin of Manufacture	China					
Quality assurance system	ISO9001					
Declaration of Conformity (held on file)	Yes					
Manufactured in accordance with	BS EN60598					
EAN	5055832947028	5055832947325	5055832947363	5055832947370	5055832947608	5055832947684

