

Blacklight BL368 Linear & Circline

F20W/T12/BL368

0000361



Range features

- BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency
- 100% improvement in effectiveness (at 368nm)
- Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)
- Performs longer and better throughout the insect season
- Same shape, structural and electrical characteristics and control circuits as standard T12, T8 or T5 tubes
- Applications
 - Insect traps, insect attraction is strongly increased
 - Restaurants, kitchens, food shops, supermarkets
 - Diazo printing machines
 - Photo Polymerisation
 - Chemical processing
 - Mineral detection
 - Various technical applications
- Directions for use
- Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m² depending on the wattage



PRODUCT OVERVIEW

Ordering number	0000361
Lamp shape	Tubular
Lamp finish	Coated
Dimmable	Yes
Cap/Base	G13
Type	T12-Special
EAN code	5410288003610
Watt (Nominal) (W)	20
Voltage (V)	57

Blacklight BL368 Linear & Circline

F20W/T12/BL368

0000361

DATA TABLE

General data

Ordering number	0000361
Average life (Nominal) (h)	10000
Lamp shape	Tubular
Lamp finish	Coated
Dimmable	Yes
Cap/Base	G13
Type	T12-Special
EAN code	5410288003610
E-number FI	4940433
Long description	BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency. 100% improvement in effectiveness (at 368nm). Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output). Performs longer and better throughout the insect season. Same shape, structural and electrical characteristics and control circuits as standard T12,T8 or T5 tubes. Applications. Insect traps, insect attraction is strongly increased. Restaurants, kitchens, food shops, supermarkets. Diazo printing machines. Photo Polymerisation. Chemical processing. Mineral detection. Various technical applications. Directions for use. Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m ²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m ² depending on the wattage
Product name	F20W/T12/BL368
Lamp mercury content (mg)	10
Control gear required	Yes
Fixture rating	Open
IEC Reference	IEC 60081
IEC Reference 2	IEC 61195
Special purpose lamp	Yes
Transformer required	No
Sales pack quantity	25

Electrical data

Watt (Rated) (W)	20
Watt (Nominal) (W)	20
Voltage (V)	57
Current (A)	0.37

Blacklight BL368 Linear & Circline

F20W/T12/BL368

0000361

Physical data

Weight (kg)	0.14
Length base to base (mm) - A	589.8
Length base to pin Min-Max - B	594.5-596.9
Lamp Length (mm) - C/L	604
Max. Lamp Diameter (mm) - D	38
Single packaging type	Box/Sleeve
Single package dimensions (L x W x H) (cm)	60.30 x 4.30 x 4.10
Outer package dimensions (L x W x H) (cm)	63.00 x 22.00 x 21.00

Blacklight BL368 Linear & Circline

F20W/T12/BL368

0000361

TECHNICAL DRAWINGS

