

## Lynx-LE

LYNX-LE 55W/840 10-WAY

0025660



### Range features



### PRODUCT OVERVIEW

Light colour	840
Technology	Compact Fluorescent
Ordering number	0025660
Energy class	A
Average life (Rated) (h)	20000
Lamp shape	Stick
Dimmable	Referring to ballast
Cap/Base	2G11
Type	Lynx LE
EAN code	5410288256603
CRI (Ra)	82
Colour temperature (K)	4000
Luminous flux (Rated) (lm)	4700
Watt (Nominal) (W)	55
Voltage (V)	101

# Lynx-LE

LYNX-LE 55W/840 10-WAY

0025660

## DATA TABLE

### General data

<b>Ordering number</b>	0025660
<b>Technology</b>	Compact Fluorescent
<b>Energy class</b>	A
<b>Average life (Nominal) (h)</b>	20000
<b>Average life (Rated) (h)</b>	20000
<b>Lamp shape</b>	Stick
<b>Dimmable</b>	Referring to ballast
<b>Cap/Base</b>	2G11
<b>Type</b>	Lynx LE
<b>EAN code</b>	5410288256603
<b>E-number FI</b>	4940122
<b>Product name</b>	LYNX-LE 55W/840 10-WAY
<b>Lamp mercury content (mg)</b>	<3.0
<b>Starting time (max) (s)</b>	<0.1
<b>Warm-up time to 60% of full light (max) (s)</b>	60
<b>Control gear required</b>	Yes
<b>IEC Reference</b>	IEC 60901
<b>IEC Reference 2</b>	IEC 61199
<b>Intended purpose</b>	General lighting
<b>Special purpose lamp</b>	No
<b>Transformer required</b>	Electronic Ballast
<b>Sales pack quantity</b>	10
<b>Rated survival factor at 2000 h 50Hz</b>	0.99
<b>Rated survival factor at 4000 h 50Hz</b>	0.98
<b>Rated survival factor at 6000 h 50Hz</b>	0.95
<b>Rated survival factor at 8000 h 50Hz</b>	0.88
<b>Rated survival factor at 12000 h 50Hz</b>	0.87
<b>Rated survival factor at 16000 h 50Hz</b>	0.78
<b>Rated survival factor at 20000 h 50Hz</b>	0.6

## Lynx-LE

LYNX-LE 55W/840 10-WAY

0025660

### Optical data

Light colour	840
CRI (Ra)	82
Colour temperature (K)	4000
Luminous flux (Rated) (lm)	4700
Luminous flux (Nominal) (lm)	4700
Ambient temperature for maximum luminous flux (°C)	25
Rated lumen maint. factor at 2000 h 50Hz	9000%
Rated lumen maint. factor at 4000 h 50Hz	8400%
Rated lumen maint. factor at 6000 h 50Hz	8200%
Rated lumen maint. factor at 8000 h 50Hz	8100%
Rated lumen maint. factor at 12000 h 50Hz	79
Rated lumen maint. factor at 16000 h 50Hz	78
Rated lumen maint. factor at 20000 h 50Hz	72

### Electrical data

kWh per 1000 hours burning time	61
Rated lamp efficacy (lm/W) 100H 50Hz at optimum temp.	82
Watt (Rated) (W)	55
Watt (Nominal) (W)	55
Voltage (V)	101
Ignition voltage (V)	350
Current (A)	0.55

### Physical data

Weight (kg)	0.15
Length base to base (mm) - A	No
Lamp Length (mm) - C/L	539.9
Single packaging type	Box/Sleeve
Single package dimensions (L x W x H) (cm)	55.20 x 4.50 x 2.50
Inner package dimensions (L x W x H) (cm)	56.20 x 10.00 x 14.00
Inner package net weight (kg)	1.50
Outer package dimensions (L x W x H) (cm)	53.00 x 58.50 x 16.50


## Lynx-LE

LYNX-LE 55W/840 10-WAY

0025660

### TECHNICAL DRAWINGS

2G11



### ENERGY LABEL

