

ToLEDo Candle

ToLEDo Candle Frosted 250LM E14 SL

0026920



Range features

- Up to 88% energy saving compared to incandescent lamps
- Instant light
- 100% retrofit - Same dimensions as incandescent equivalent
- Suitable for replacement of up to 25W and 40W incandescent lamps
- Uniform light distribution
- Available in Homelight (2700K)
- Good colour rendering (CRI 80+)
- Average rated life 25,000 hrs



PRODUCT OVERVIEW

Light colour	Homelight
Technology	LED
Ordering number	0026920
Average life (Rated) (h)	25000
Energy class	A+
Lamp shape	Candle
Lamp finish	Frosted
Dimmable	No
Cap/Base	E14
Type	ToLEDo Candle
EAN code	5410288269207
CRI (Ra)	80
Colour temperature (K)	2700
Luminous flux (Rated) (lm)	250
Watt (Nominal) (W)	4
Equivalent watt (W)	25
Voltage (V)	220-240

ToLEDo Candle

ToLEDo Candle Frosted 250LM E14 SL

0026920

DATA TABLE

General data

Ordering number	0026920
Dry applications use only	Yes
Technology	LED
Energy saving lamp	Yes
Energy class	A+
Average life (Rated) (h)	25000
Average life (Nominal) (h)	25000
Lamp finish	Frosted
Lamp shape	Candle
Dimmable	No
Cap/Base	E14
Type	ToLEDo Candle
EAN code	5410288269207
E-number FI	4740193
Long description	Up to 88% energy saving compared to incandescent lamps. Instant light. 100% retrofit - Same dimensions as incandescent equivalent. Suitable for replacement of up to 25W and 40W incandescent lamps. Uniform light distribution. Available in Homelight (2700K). Good colour rendering (CRI 80+). Average rated life 25,000 hrs
Product name	ToLEDo Candle Frosted 250LM E14 SL
Lamp mercury content (mg)	0
Starting time (max) (s)	0.05
Warm-up time to 60% of full light (max) (s)	< 1s => 60%
Control gear required	No
Intended purpose	No
No. of switching cycles before premature failure (min)	50000
Special purpose lamp	No
Sales pack quantity	1
Optimal operating condition (°C)	25

Optical data

Light colour	Homelight
CRI (Ra)	80
Colour temperature (K)	2700
Luminous flux (Rated) (lm)	250
Lumen maintenance at end of nominal life (%)	70
Luminous flux (Nominal) (lm)	250

ToLEDo Candle

ToLEDo Candle Frosted 250LM E14 SL

0026920

Electrical data

kWh per 1000 hours burning time	4
Equivalent watt (W)	25
Watt (Rated) (W)	4
Watt (Nominal) (W)	4
Voltage (V)	220-240
Current (A)	0.024
Lamp power factor	0.7

Physical data


Weight (kg)	0.05
Lamp Length (mm) - C/L	104
Max. Lamp Diameter (mm) - D	38
Single packaging type	Box/Sleeve
Single package dimensions (L x W x H) (cm)	11.90 x 4.80 x 4.80
Inner package dimensions (L x W x H) (cm)	15.50 x 10.50 x 13.40
Inner package net weight (kg)	0.27
Outer package dimensions (L x W x H) (cm)	55.00 x 32.60 x 15.40

ToLEDo Candle

ToLEDo Candle Frosted 250LM E14 SL

0026920

TECHNICAL DRAWINGS



ENERGY LABEL

□