

POWERSTAR HQI/HCI POWERBALL HCI

Technical Information


SEE THE WORLD IN A NEW LIGHT

OSRAM






- All rights reserved. No part of this document may be reproduced, copied or distributed in any form (printed matter, photocopy, etc.) without the written permission of HID M-M, OSRAM Germany.
- This brochure supersedes all previous editions.
- All dimensions, weights, specifications and graphic representations are given without obligation. All design features, dimensions and technical specifications are subject to change without notice.

POWERSTAR® HCI®




HCI 35 W

		WDL	TC
		T	TC
		UVS	UVS
Type		MT-35/30/1B-H	MT-35/30/1B-H
ILCOS		90/S-G12-20/100	90/S-G8.5-15/81
Lamp wattage	W	39	39
Lamp voltage	V	90	90
Ignition voltage min./max.	kVs	3.6/5	3.6/4.5
Lamp current	A	0.5	0.5
Nominal luminous flux	lm	3300	3300
Luminous efficacy	[lm/W]	85	85
Average luminance	cd/cm ²	–	–
Light colour/Colour appearance		WDL	WDL
Colour temperature	K	3000	3000
Colour rendering index	R _a	81	81
NIOSH Skin	h	> 21	> 21
ACGIH UV output	mW	< 0.4	< 0.4
Base		G12	G8.5
Diameter d	mm	19	15
Length max. l	mm	100	81
LCL a	mm	56	52
Burning position		universal	universal
Average lamp life	h	9000	9000
Max. perm. outer bulb temp.	°C	450	450
Max. perm. base edge temp.	°C	280	280
PF corr. cap. at 50 Hz	µF	6	6
Lamp reference		HCI-T 35/WDL	HCI-TC 35/WDL
EAN 4050300		468013	581378
Standard pack	Qty	12	12
Figure	No.	1	2
Circuit (see page 28)	Fig. no.	2/5	2/5





POWERBALL® HCI®




HCI 70 W

		WDL					
		TS <small>New</small>	T <small>New</small>	TC <small>New</small>	TT <small>New</small>	E/P clear <small>New</small>	E/P coated <small>New</small>
Type		UVS, PB	UVS, PB	UVS, PB	PB	PB	PB
ILCOS		MD-70/30/1B-H 90/S-RX7s- 21/114	MT-70/30/1B-H 90/S-G12- 20/100	MT-70/30/1B-H 90/S-G8.5- 15/82	MT-70/30/1B-H 90/S-E27- 30/150	MCS-70/30/1B-H 90/S-E27- 54/138	MES-70/42/1A-H 99/S-E27- 54/138
Lamp wattage	W	72	72	72	70	70	70
Lamp voltage	V	95	100	95	90	90	90
Ignition voltage min./max.	kVs	3.6/4.5	3.6/5	3.6/4.5	2.3/4.5	3.6/4.5	3.6/4.5
Lamp current	A	0.96	0.98	0.95	1	0.98	0.98
Nominal luminous flux	lm	6600	6700	5700	6500	6000	5700
Luminous efficacy	lm/W	92	94	78	93	86	81
Average luminance	cd/cm ²	–	–	–	–	–	–
Light colour/Colour appearance		WDL	WDL	WDL	WDL	WDL	WDL
Colour temperature	K	3000	3000	3000	3000	3000	3000
Colour rendering index	R _a	88	87	≥ 90	87	87	87
NIOSH Skin	h	> 18	> 47	> 24	> 47	> 47	> 47
ACGIH UV output	mW	< 0.45	< 0.18	< 0.35	< 0.18	< 0.18	< 0.18
Base		RX7s	G12	G8.5	E27	E27	E27
Diameter d	mm	21	19	15	30	54	54
Length max. l	mm	114.2	100	81	150	138	138
LCL a	mm	57	56	52	102	86	–
Burning position		p 45	universal	universal	universal	universal	universal
Average lamp life	h	9000	9000	9000	9000	9000	9000
Max. perm. outer bulb temp.	°C	500	500	450	310	275	275
Max. perm. base edge temp.	°C	280	280	300	210	190	190
PF corr. cap. at 50 Hz	µF	12	12	12	12	12	12
Lamp reference		HCI-TS 70/WDL PB	HCI-TS 70/WDL PB	HCI-TC 70/WDL PB	HCI-TT 70/WDL PB	HCI-E/P 70/WDL PB clear	HCI-E/P 70/WDL PB coated
EAN 4050300		784069	784021	793566	784120	780856	781815
Standard pack	Qty	12	12	12	12	12	12
Figure	No.	1	2	3	4	5	5
Circuit (see page 28)	Fig. no.	2/5	2/5	2/5	2/5	2/5	2/5







POWERSTAR® HCI®


POWERSTAR® HQI®



		HCI 70 W	HQI 70 W	HQI 70 W	HQI 70 W	HQI 70 W
		WDL		E clear		E coated
Type		TC	TS	T	E clear	E coated
ILCOS		UVS	UVS	UVS		
		MT-70/30/1B-H 90/S-G8.5- 15/82	MD-70/30/1B-H 97/S-RX7s-20/ 114.2/P 45	MT-70/30/1B-H 95/S-G12-25/84	MCS-70/32/1B-H 98/S-E27-55/144	MES-70/31/1B-H 98/S-E27-55/144
Lamp wattage	W	72	75	75	73	73
Lamp voltage	V	90	95	95	95	95
Ignition voltage min./max.	kVs	3.6/4.5	3.6/4.5	3.6/5	3.6/4.5	3.6/4.5
Lamp current	A	1	1	1	0.95	0.95
Nominal luminous flux	lm	6600	5000	5200	4700	4900
Luminous efficacy	lm/W	92	64	69	64	67
Average luminance	cd/cm ²	–	1500	1500	1500	21
Light colour/Colour appearance		WDL	WDL	WDL	WDL	WDL
Colour temperature	K	3000	3000	3000	3200	3100
Colour rendering index	R _a	81	76	76	70	70
NIOSH	h	> 24	> 23	> 17.3	> 134	> 150
ACGIH UV output	mW	< 0.35	< 0.36	< 0.48	< 0.06	< 0.06
Base		G8.5	RX7s	G12	E27	E27
Diameter d	mm	15	20	25	55	55
Length max. l	mm	81	114.2	84	144	144
LCL a	mm	52	57	56	92	–
Burning position		universal	p 45	universal	universal	universal
Average lamp life	h	9000	9000	9000	9000	9000
Max. perm. outer bulb temp.	°C	450	500	500	275	275
Max. perm. base edge temp.	°C	300	280	280	190	190
PF corr. cap. at 50 Hz	µF	12	12	12	12	12
Lamp reference		HCI-TC 70/WDL	HQI-TS 70/WDL	HQI-T 70/WDL	HQI-E 70/WDL	HQI-E 70/WDL
EAN 4050300		UVS 581392	UVS 412955	UVS 412993	clear 397788	coated 397801
Standard pack	Qty	12	12	12	20	20
Figure	No.	2	1	3	4	5
Circuit (see page 28)	Fig. no.	2/5	2/5	2/5	2/5	2/5





POWERSTAR® HCI®




HCI 70 W

Type		NDL	T	TC	E/P clear	E/P coated
		TS	UVS	UVS	UVS	
ILCOS		MD-70/42/1A-H 90/S-RX7s- 21/114/P 45	MT-70/42/1A-H 90/S-G12-20/100	MT-70/42/1A-H 90/S-G8.5-15/81	MCS-70/42/1A-H 90/S-E27-54/138	MES-70/42/1A-H 99/S-E27-54/138
Lamp wattage	W	72	72	72	72	72
Lamp voltage	V	95	90	90	100	100
Ignition voltage min./max.	kVs	3.6/4.5	3.6/5	3.6/4.5	3.6/4.5	3.6/4.5
Lamp current	A	0.95	1	0.95	0.98	0.98
Nominal luminous flux	lm	5700	5800	6000	5400	5200
Luminous efficacy	lm/W	79	81	84	75	72
Average luminance	cd/cm ²	–	–	–	–	–
Light colour/Colour appearance		NDL	NDL	NDL	NDL	NDL
Colour temperature	K	4200	4200	4200	4200	4200
Colour rendering index	R _a	92	92	94	90	90
NIOSH	h	> 29.7	> 27	> 22	–	–
ACGIH UV output	mW	< 0.28	< 0.31	< 0.37	–	–
Base		RX7s	G12	G8.5	E27	E27
Diameter d	mm	21	19	15	54	54
Length max. l	mm	114.2	100	81	138	138
LCL a	mm	57	56	52	86	–
Burning position		p 45	universal	universal	universal	universal
Average lamp life	h	9000	9000	9000	9000	9000
Max. perm. outer bulb temp.	°C	500	500	450	275	275
Max. perm. base edge temp.	°C	280	280	300	190	190
PF corr. cap. at 50 Hz	µF	12	12	12	12	12
Lamp reference		HCI-TS 70/NDL	HCI-TS 70/NDL	HCI-TC 70/NDL	HCI-E/P 70/NDL clear	HCI-E/P 70/NDL coated
EAN 4050300		467917	467832	637693	637556	637631
Standard pack	Qty	12	12	12	12	12
Figure	No.	1	2	3	4	4
Circuit (see page 28)	Fig. no.	2/5	2/5	2/5	2/5	2/5






POWERSTAR® HQI®




HQI 70 W

Type	NDL				
	TS	T	E clear	E coated	D
	UVS	UVS			UVS
ILCOS	MD-70/42/1B-H 85/S-RX7s- 20/114.2/P 45	MT-70/42/1B-H 95/S-G12-25/84	MCS-70/40/1B-H 85/S-E27-55/144	MES-70/38/1B-H 85/S-E27-55/144	MD-70/52/1B-H 95/S-RX7s- 20/114.2/P 45
Lamp wattage	W 73	75	73	73	75
Lamp voltage	V 85	100	90	90	110
Ignition voltage min./max.	kVs 3.6/4.5	3.6/5	3.6/4.5	3.6/4.5	3.6/4.5
Lamp current	A 1	1	1	1	1
Nominal luminous flux	lm 5500	5500	5200	4900	5000
Luminous efficacy	lm/W 75	73	71	67	67
Average luminance	cd/cm ² 1650	-	1600	25	1500
Light colour/Colour appearance	NDL	NDL	NDL	NDL	D
Colour temperature	K 4000	4200	4000	3800	5200
Colour rendering index	R _a 83	84	70	70	85
NIOSH	h > 7	> 58	> 179	> 179	> 16
ACGIH UV output	mW < 1.26	< 0.14	< 0.05	< 0.05	< 0.52
Base	RX7s	G12	E27	E27	RX7s
Diameter d	mm 20	25	55	55	20
Length max. l	mm 114.2	84	144	144	114.2
LCL a	mm 57	56	92	-	57
Burning position	p 45	universal	universal	universal	p 45
Average lamp life	h 9000	9000	9000	9000	9000
Max. perm. outer bulb temp.	°C 500	500	275	275	500
Max. perm. base edge temp.	°C 280	280	190	190	280
PF corr. cap. at 50 Hz	µF 12	12	12	12	12
Lamp reference	HQI-TS 70/NDL UVS	HQI-T 70/NDL UVS	HQI-E 70/NDL clear	HQI-E 70/NDL coated	HQI-TS 70/D UVS
EAN 4050300	421931	488424	397825	397849	437521
Standard pack	Qty 12	12	20	20	12
Figure	No. 1	2	3	4	1
Circuit (see page 28)	Fig. no. 2/5	2/5	2/5	2/5	2/5







POWERBALL® HCI®


POWERSTAR® HQI®



	HCI 100 W		HQI 100 W		
	WDL	E/P clear <i>New</i>	E/P coated <i>New</i>	WDL	E coated
Type	PB	PB	PB	PB	PB
ILCOS	MCS-100/30/1B-H 100/S-E27-54/141	MES-100/30/1B-H 100/S-E27-54/141	MCS-100/30/1B-H 100/S-E27-55/144	MES-100/29/1B-H 100/S-E27-55/144	MES-100/29/1B-H 100/S-E27-55/144
Lamp wattage	W	100	100	100	100
Lamp voltage	V	100	100	95	95
Ignition voltage min./max.	kVs	3.6/4.5	3.6/4.5	3.6/4.5	3.6/4.5
Lamp current	A	1.1	1.1	1.1	1.1
Nominal luminous flux	lm	9000	8600	8500	8000
Luminous efficacy	lm/W	90	86	85	80
Average luminance	cd/cm ²	–	–	1700	28
Light colour/Colour appearance	WDL	WDL	WDL	WDL	WDL
Colour temperature	K	3000	3000	3000	2900
Colour rendering index	R _a	90	86	85	80
NIOSH	h	> 500	> 500	> 231	> 231
ACGIH UV output	mW	< 0.02	< 0.02	< 0.04	< 0.04
Base		E27	E27	E27	E27
Diameter d	mm	54	54	55	55
Length max. l	mm	141	141	144	144
LCL a	mm	92	–	92	–
Burning position		universal	universal	universal	universal
Average lamp life	h	9000	9000	9000	9000
Max. perm. outer bulb temp.	°C	275	275	275	275
Max. perm. base edge temp.	°C	190	190	190	190
PF corr. cap. at 50 Hz	µF	16	16	16	16
Lamp reference		HCI-E/P 100/WDL PB clear	HCI-E/P 100/WDL PB coated	HQI-E 100/WDL clear	HQI-E 100/WDL coated
EAN 4050300		941875	941899	351537	351551
Standard pack	Qty	12	12	20	20
Figure	No.	1	1	2	3
Circuit (see page 28)	Fig. no.	2	2	2	2





POWERSTAR® HQI®




HQI 100 W

		NDL	
		E clear	E coated
Type			
ILCOS		MCS-100/40/1B-H 115/S-E27-55/144	MES-100/38/1B-H 115/S-E27-55/144
Lamp wattage	W	100	100
Lamp voltage	V	95	95
Ignition voltage min./max.	kVs	3.6/4.5	3.6/4.5
Lamp current	A	1.1	1.1
Nominal luminous flux	lm	7800	7300
Luminous efficacy	lm/W	78	73
Average luminance	cd/cm ²	1800	30
Light colour/Colour appearance		NDL	NDL
Colour temperature	K	4000	3800
Colour rendering index	R _a	70	70
NIOSH	h	> 305	> 306
ACGIH UV output	mW	< 0.03	< 0.04
Base		E27	E27
Diameter d	mm	55	55
Length max. l	mm	144	144
LCL a	mm	92	-
Burning position		universal	universal
Average lamp life	h	9000	9000
Max. perm. outer bulb temp.	°C	275	275
Max. perm. base edge temp.	°C	190	190
PF corr. cap. at 50 Hz	µF	16	16
Lamp reference		HQI-E 100/NDL clear	HQI-E 100/NDL coated
EAN 4050300		345871	345833
Standard pack	Qty	20	20
Figure	No.	1	2
Circuit (see page 28)	Fig. no.	2	2





POWERBALL® HCI®




HCI 150 W

Type	WDL				
	TS ^{New}	T ^{New}	TT ^{New}	E/P clear ^{New}	E/P coated ^{New}
	UVS, PB	UVS, PB	PB	UVS, PB	UVS, PB
ILCOS	MD-150/30/1B-H 100/S-RX7s-24- 24/132/P 45	MT-150/30/1B-H 100/S-G12-20/105	MT-150/30/1B-H 97/S-E40-46/204	MCS-150/30/1B-H 109/S-E27-54/138	MES-150/30/1B-H 109/S-E27-54/138
Lamp wattage	W 147	147	145	145	145
Lamp voltage	V 100	100	95	95	95
Ignition voltage min./max.	kVs 3.6/4.5	3.6/5	3/4.5	3.6/4.5	3.6/4.5
Lamp current	A 1.8	1.8	1.8	1.8	1.8
Nominal luminous flux	lm 14800	14500	14500	13500	13000
Luminous efficacy	lm/W 100	99	100	93	90
Average luminance	cd/cm ² -	-	-	-	-
Light colour/Colour appearance	WDL	WDL	WDL	WDL	WDL
Colour temperature	K 3000	3000	3000	3000	3000
Colour rendering index	R _a 91	89	90	90	90
NIOSH	h > 238	> 138	> 208	-	-
ACGIH UV output	mW < 0.4	< 0.06	< 0.04	-	-
Base	R7s-24	G12	E40	E27	E27
Diameter d	mm 23	23	46	54	54
Length max. l	mm 132	105	204	138	138
LCL a	mm 66	56	132	86	-
Burning position	universal	universal	universal	universal	universal
Average lamp life	h 9000	9000	9000	9000	9000
Max. perm. outer bulb temp.	°C 650	650	310	300	300
Max. perm. base edge temp.	°C 280	280	210	190	190
PF corr. cap. at 50 Hz	µF 20	20	20	20	20
Lamp reference	HCI-TS 150/WDL	HCI-T 150/WDL	HCI-TT 150/WDL	HCI-E/P 150/WDL	HCI-E/P 150/WDL
	PB	PB	PB	PB clear	PB coated
EAN 4050300	783987	783949	784144	780870	781846
Standard pack	Qty 12	12	12	12	12
Figure	No. 1	2	3	4	4
Circuit (see page 28)	Fig. no. 2/5	2/5	2/5	2/5	2/5







POWERSTAR® HQI®




HQI 150 W

		WDL			
		TS	T	E clear	E coated
Type		UVS	UVS		
ILCOS		MD-150/30/1B-H 95/S-RX7s-24- 23/132/P 45	MT-150/30/1B-H 100/S-G12-25/84	MCS-150/29/1B-H 100/S-E27-54/141	MES-150/29/1B-H 100/S-E27-55/144
Lamp wattage	W	150	150	150	150
Lamp voltage	V	95	100	95	95
Ignition voltage min./max.	kVs	3.6/4.5	3.6/5	3.6/4.5	3.6/4.5
Lamp current	A	1.8	1.8	1.8	1.8
Nominal luminous flux	lm	11000	13000	12000	12000
Luminous efficacy	lm/W	73	87	80	80
Average luminance	cd/cm ²	2400	—	—	—
Light colour/Colour appearance		WDL	WDL	WDL	WDL
Colour temperature	K	3000	3000	2900	2900
Colour rendering index	R _a	76	77	70	70
NIOSH	h	> 41	> 22	> 50	> 50
ACGIH UV output	mW	< 0.2	< 0.4	< 0.17	< 0.17
Base		RX7s-24	G12	E27	E27
Diameter d	mm	23	25	55	55
Length max. l	mm	132	84	144	144
LCL a	mm	66	56	92	—
Burning position		p 45	universal	universal	universal
Average lamp life	h	12000	9000	9000	9000
Max. perm. outer bulb temp.	°C	650	550	275	275
Max. perm. base edge temp.	°C	280	280	140	140
PF corr. cap. at 50 Hz	µF	20	20	20	20
Lamp reference		HQI-TS 150/WDL UVS	HQI-T 150/WDL UVS	HQI-E 150/WDL clear	HQI-E 150/WDL coated
EAN 4050300		412979	413013	433974	433998
Standard pack	Qty	12	12	20	20
Figure	No.	1	2	3	4
Circuit (see page 28)	Fig. no.	2/5	2/5	2/5	2/5






POWERSTAR® HCI®




HCI 150 W






		NDL			
		TS	T	E/P clear	E/P coated
Type		UVS	UVS	UVS	UVS
ILCOS		MD-150/42/1A-H 100/S-RX7s-24- 24/132/P 45	MT-150/42/1A-H 100/S-G12-20/105	MCS-150/42/1A-H 95/S-E27-54/138	MES-150/42/1A-H 95/S-E27-54/138
Lamp wattage	W	147	147	150	150
Lamp voltage	V	100	100	100	100
Ignition voltage min./max.	kVs	3.6/4.5	3.6/5	3.6/4.5	3.6/4.5
Lamp current	A	1.8	1.8	1.8	1.8
Nominal luminous flux	lm	13400	12700	12500	12000
Luminous efficacy	lm/W	91	86	83	83
Average luminance	cd/cm ²	–	–	–	–
Light colour/Colour appearance		NDL	NDL	NDL	NDL
Colour temperature	K	4200	4200	4200	4200
Colour rendering index	R _a	91	88	97	97
NIOSH	h	> 26	> 70	> 50	> 50
ACGIH UV output	mW	< 0.32	< 0.12	< 0.17	< 0.17
Base		RX7s-24	G12	E27	E27
Diameter d	mm	24	19	54	54
Length max. l	mm	132	105	138	138
LCL a	mm	66	56	86	–
Burning position		p 45	universal	universal	universal
Average lamp life	h	9000	9000	9000	9000
Max. perm. outer bulb temp.	°C	650	550	300	300
Max. perm. base edge temp.	°C	280	280	190	190
PF corr. cap. at 50 Hz	µF	20	20	20	20
Lamp reference		HCI-TS 150/NDL	HCI-T 150/NDL	HCI-E/P 150/NDL clear	HCI-E/P 150/NDL coated
EAN 4050300		467979	467870	637594	637679
Standard pack	Qty	12	12	12	12
Figure	No.	1	2	3	3
Circuit (see page 28)	Fig. no.	2/5	2/5	2/5	2/5



POWERSTAR® HQI®




HQI 150 W						
		NDL	T	E clear	E coated	D
Type		TS	T	E clear	E coated	TS
ILCOS		UVS	UVS	E clear	E coated	UVS
		MD-150/42/1B-H 90/S-RX7s-24- 23/132/P 45	MT-150/42/1B-H 95/S-G12-25/84	MCS-150/40/1B-H 100/S-E27-55/144	MES-150/38/1B-H 100/S-E27-55/144	MD-150/52/1B-H 100/S-RX7s-24- 23/132/P 45
Lamp wattage	W	150	150	150	150	150
Lamp voltage	V	90	100	85	85	100
Ignition voltage min./max.	kVs	3.6/4.5	3.6/5	3.6/4.5	3.6/4.5	3.6/4.5
Lamp current	A	1.8	1.8	1.8	1.8	1.8
Nominal luminous flux	lm	11250	13000	11400	10500	11000
Luminous efficacy	lm/W	75	87	76	70	73
Average luminance	cd/cm ²	1500	-	-	-	1500
Light colour/Colour appearance		NDL	NDL	NDL	NDL	D
Colour temperature	K	4200	4200	4000	3800	5200
Colour rendering index	R _a	85	85	80	86	88
NIOSH	h	> 10.2	> 17	> 50	> 247	> 11.7
ACGIH UV output	mW	< 0.8	< 0.5	< 0.17	< 0.03	< 0.7
Base		RX7s-24	G12	E27	E27	RX7s-24
Diameter d	mm	23	25	55	55	23
Length max. l	mm	132	84	144	144	132
LCL a	mm	66	56	92	-	66
Burning position		p 45	universal	universal	universal	p 45
Average lamp life	h	12000	9000	9000	9000	12000
Max. perm. outer bulb temp.	°C	650	550	275	275	650
Max. perm. base edge temp.	°C	280	280	190	190	280
PF corr. cap. at 50 Hz	µF	20	20	20	20	20
Lamp reference		HQI-TS 150/NDL UVS	HQI-T 150/NDL UVS	HQI-E 150/NDL clear	HQI-E 150/NDL coated	HQI-TS 150/D UVS
EAN 4050300		362380	488448	434018	434032	437545
Standard pack	Qty	12	12	20	20	12
Figure	No.	1	2	3	4	1
Circuit (see page 28)	Fig. no.	2/5	2/5	2/5	2/5	2/5






POWERBALL® HCI®


POWERSTAR® HQI®



		HCI 250 W			HQI 250 W
		WDL			
		TS ^{New}	T ^{New}	E coated ^{New}	TS
Type		PB	PB	PB	PB
ILCOS		MD-250/30/1B-H 102/S-Fc2- 25/163	MT-250/30/1B-H 110/S-E40- 46/226	ME-250/30/1B-H 100/S-E40- 90/226	MD-250/32/1B-H 104/S-Fc2- 25/163/P 45
Lamp wattage	W	242	248	241	250
Lamp voltage	V	100	105	95	110
Ignition voltage min./max.	kVs	3.6/4.5	3.6/4.5	3.6/4.5	3.6/4.5
Lamp current	A	2.9	2.9	2.9	2.8
Nominal luminous flux	lm	24200	25800	24100	22000
Luminous efficacy	lm/W	100	104	100	88
Average luminance	cd/cm ²	–	–	–	1600
Light colour/Colour appearance		WDL	WDL	WDL	WDL
Colour temperature	K	3000	3000	3000	3200
Colour rendering index	R _a	91	89	88	80
NIOSH	h	> 56	> 193	> 81	> 12
ACGIH UV output	mW	< 0.15	< 0.04	< 0.1	< 0.68
Base		Fc2	E40	E40	Fc2
Diameter d	mm	25	46	90	25
Length max. l	mm	163	226	226	163
LCL a	mm	81.5	150	–	81.5
Burning position		universal	universal	universal	p 45
Average lamp life	h	12000	12000	12000	12000
Max. perm. outer bulb temp.	°C	650	500	400	650
Max. perm. base edge temp.	°C	300	250	250	300
PF corr. cap. at 50 Hz	µF	32	32	32	32
Lamp reference		HCI-TS 250/WDL PB	HCI-T 250/WDL PB	HCI-E 250/WDL PB	HCI-TS 250/WDL
EAN 4050300		637730	636849	636825	436012
Standard pack	Qty	12	12	12	12
Figure	No.	1	2	3	4
Circuit (see page 28)	Fig. no.	2/5	2/5	2	2







POWERSTAR® HQI®




HQI 250 W

Type		NDL	D	T	E coated	E/P coated
		TS	TS			
		UVS	UVS			
ILCOS		MD-250/42/1B-H 100/S-Fc2- 25/163/P 45	MD-250/51/1A-H 100/S-Fc2- 25/163/P 45	MT-250/53/1A-H 100/S-E40- 40/225	ME-250/52/1A-H 100/S-E40- 90/226	MES-250/60/1A-H 98/S-E40- 90/226
Lamp wattage	W	250	250	250	250	250
Lamp voltage	V	100	100	100	100	100
Ignition voltage min./max.	kVs	3.6/4.5	3/4.5	3/4.5	3/4.5	3/4.5
Lamp current	A	3	3	3	3	3
Nominal luminous flux	lm	20000	20000	20000	19000	17000
Luminous efficacy	lm/W	80	80	80	76	71
Average luminance	cd/cm ²	1350	1500	1100	20	—
Light colour/Colour appearance		NDL	D	D	D	D
Colour temperature	K	4200	5100	5300	5200	6000
Colour rendering index	R _a	88	93	90	90	90
NIOSH	h	> 12	> 18	> 107	> 27	> 69
ACGIH UV output	mW	< 0.71	< 0.46	< 0.08	< 0.31	< 0.12
Base		Fc2	Fc2	E40	E40	E40
Diameter d	mm	25	25	46	90	90
Length max. l	mm	163	163	225	226	226
LCL a	mm	81.5	81.5	150	—	—
Burning position		p 45	p 45	universal	universal	universal
Average lamp life	h	12000	12000	12000	12000	12000
Max. perm. outer bulb temp.	°C	650	650	500	400	400
Max. perm. base edge temp.	°C	300	300	250	250	250
PF corr. cap. at 50 Hz	µF	32	32	32	32	32
Lamp reference		HQI-TS 250/NDL	HQI-TS 250/D	HQI-T 250/D	HQI-E 250/D	HQI-E/P 250/D
EAN 4050300		436036	436050	015293	015248	637457
Standard pack	Qty	12	12	12	12	12
Figure	No.	1	1	2	3	3
Circuit (see page 28)	Fig. no.	2/3	2	2	2	2






POWERSTAR® HQI®




HQI 400 W

Type		NDL		D		
		TS	TS	TS	BT	BT
			NAV-VG	HQI-VG	NAV-VG	HQI-VG
ILCOS		MD-400/42/1B-H 118/S-Fc2- 31/206/P 45	MD-400/52/1A-H 128/S-Fc2- 31/206/P 45	MD-400/56/1A-H 120/S-Fc2- 31/206/H 45	MT-400/61/1A-H 122/S-E40- 62/285	MT-400/61/1A-H 122/S-E40- 62/285
Lamp wattage	W	400	400	350	420	360
Lamp voltage	V	120	125	120	120	120
Ignition voltage min./max.	kVs	3/4.5	3/4.5	3/4.5	3/4.5	3/4.5
Lamp current	A	4.1 ¹⁾	4.1	3.6	4	3.5
Nominal luminous flux	lm	35000	36000	28000	32000	25000
Luminous efficacy	lm/W	88	90	80	76	69
Average luminance	cd/cm ²	1200	1400	1100	1400	650
Light colour/Colour appearance		NDL	D	D	D	D
Colour temperature	K	4200	5200	5600	5200	6100
Colour rendering index	R _a	85	93	90	90	90
NIOSH	h	> 11 min	> 11 min	> 11 min	> 136	> 136
ACGIH UV output	mW	< 47	< 46	< 46	< 0.06	< 0.06
Base		Fc2	Fc2	Fc2	E40	E40
Diameter d	mm	31	31	31	62	62
Length max. l	mm	206	206	206	285	285
LCL a	mm	103	103	103	175	175
Burning position		p 45	p 45	p 45	universal	universal
Average lamp life	h	12000	12000	12000	12000	12000
Max. perm. outer bulb temp.	°C	650	650	650	500	500
Max. perm. base edge temp.	°C	300	300	300	250	250
PF corr. cap. at 50 Hz	µF	45	45	35	45	35
Lamp reference		HQI-TS 400/NDL	HQI-TS 400/D	HQI-TS 400/D	HQI-BT 400/D	HQI-BT 400/D
EAN 4050300		304090	015385	015385	468471	468471
Standard pack	Qty	12	12	12	12	12
Figure	No.	1	1	1	2	2
Circuit (see page 28)	Fig. no.	2	2	2	2	2





1) Operate only with NAV control gear

POWERSTAR® HQI®




HQI 400 W

		D			
		E coated	E coated	E/P coated	E/P coated
Type		NAV-VG	HQI-VG	NAV-VG	HQI-VG
ILCOS		ME-400/59/1A-H 130/S-E40-120/290	ME-400/59/1A-H 110/S-E40-120/290	MES-400/45/1A-H 110/S-E40-120/290	MES-400/45/1A-H 115/S-E40-120/290
Lamp wattage	W	460	400	400	400
Lamp voltage	V	130	110	110	115
Ignition voltage min./max.	kVs	3/4.5	3/4.5	3/4.5	3/4.5
Lamp current	A	3.8	3.6	3.8	3.5
Nominal luminous flux	lm	30000	26000	27000	23000
Luminous efficacy	lm/W	76	72	68	67
Average luminance	cd/cm ²	17	10	–	–
Light colour/Colour appearance		D	D	D	D
Colour temperature	K	5900	5800	4500	5000
Colour rendering index	R _a	90	90	90	90
NIOSH	h	> 18	> 18	> 79	> 79
ACGIH UV output	mW	< 0.46	< 0.46	< 0.11	< 0.11
Base		E40	E40	E40	E40
Diameter d	mm	120	120	120	120
Length max. l	mm	290	290	290	290
LCL a	mm	–	–	–	–
Burning position		universal	universal	universal	universal
Average lamp life	h	12000	12000	12000	12000
Max. perm. outer bulb temp.	°C	400	400	400	400
Max. perm. base edge temp.	°C	250	250	250	250
PF corr. cap. at 50 Hz	µF	45	35	45	35
Lamp reference		HQI-E 400/D	HQI-E 400/D	HQI-E/P 400/D	HQI-E/P 400/D
EAN 4050300		019727	019727	637433	637433
Standard pack	Qty	12	12	12	12
Figure	No.	1	1	1	1
Circuit (see page 28)	Fig. no.	2	2	2	2





POWERSTAR® HQI®




HQI 400 W

		N					
		T	T	E clear	E clear	E coated	E coated
Type		NAV-VG	HQI-VG	NAV-VG	HQI-VG	NAV-VG	HQI-VG
ILCOS		MT-400/37/2B-H 124/S-E40- 46/275/P 45	MT-400/38/2B-H 120/S-E40- 46/285/H 45	MC-400/38/2A-H 115/S-E40- 120/290	MC-400/36/2A-H 115/S-E40- 120/290	ME-400/40/2A-H 115/S-E40- 120/290	ME-400/38/2A-H 115/S-E40- 120/290
Lamp wattage	W	420	380	420	420	460	460
Lamp voltage	V	125	120	125	120	125	120
Ignition voltage min./max.	kVs	3.6/4.5	3.6/4.5	3.6/4.5	3.6/4.5	3.6/4.5	3.6/4.5
Lamp current	A	4.1	3.6	4.2	3.5	4.2	3.5
Nominal luminous flux	lm	42000	34000	45000	36000	43000	34000
Luminous efficacy	lm/W	100	89	112	97	107	92
Average luminance	cd/cm ²	–	–	–	–	–	–
Light colour/Colour appearance	N	N	N	N	N	N	N
Colour temperature	K	3700	3800	4000	3600	4000	3600
Colour rendering index	R _a	65	65	70	65	70	65
NIOSH	h	–	–	–	–	–	–
ACGIH UV output	mW	–	–	–	–	–	–
Base		E40	E40	E40	E40	E40	E40
Diameter d	mm	46	46	120	120	120	120
Length max. l	mm	275	275	290	290	290	290
LCL a	mm	175	175	198	198	–	–
Burning position		p 45	p 45	universal	universal	universal	universal
Average lamp life	h	12000	12000	12000	12000	12000	12000
Max. perm. outer bulb temp.	°C	500	500	500	500	500	500
Max. perm. base edge temp.	°C	250	250	250	250	250	250
PF corr. cap. at 50 Hz	µF	45	35	45	35	45	35
Lamp reference		HQI-T 400/N	HQI-T 400/N	HQI-E 400/N clear	HQI-E 400/N clear	HQI-E 400/N	HQI-E 400/N
EAN 4050300		324647	624647	292632	292632	305431	305431
Standard pack	Qty	12	12	12	12	12	12
Figure	No.	1	1	2	2	3	3
Circuit (see page 28)	Fig. no.	2	2	2	2	2	2




POWERSTAR® HQI®




HQI 400 W

		BLUE	GREEN	MAGENTA
		T	T	T
Type				
ILCOS		–	–	–
Lamp wattage	W	360	360	440
Lamp voltage	V	120	120	120
Ignition voltage min./max.	kVs	3/4.5	3/4.5	4/4.5
Lamp current	A	3.6	3.6	4.6
Nominal luminous flux	lm	uncertain	uncertain	uncertain
Luminous efficacy	lm/W	uncertain	uncertain	uncertain
Average luminance	cd/cm ²	–	–	–
Light colour/Colour appearance				
Colour temperature	K	monochr.	monochr.	monochr.
Colour rendering index	R _a	–	–	–
NIOSH	h	–	–	–
ACGIH UV output	mW	–	–	–
Base		E40	E40	E40
Diameter d	mm	46	46	46
Length max. l	mm	260	260	273
LCL a	mm	175	175	175
Burning position		universal	universal	p 30
Average lamp life	h	–	–	–
Max. perm. outer bulb temp.	°C	500	500	500
Max. perm. base edge temp.	°C	250	250	250
PF corr. cap. at 50 Hz	µF	45	45	45
Lamp reference		HQI-T 400 BLUE	HQI-T 400 GREEN	HQI-T 400 MAGENTA
EAN 4050300		258300	258287	649535
Standard pack	Qty	12	12	12
Figure	No.	1	1	1
Circuit (see page 28)	Fig. no.	2	2	2







POWERSTAR® HQI®




HQI 1000 W

		NDL	D	N	
		TS	TS	T	E coated
		/S	/S		
Type					
ILCOS		MN-1000/42/1B-H 120/S-cable lug- 36/187/P 15	MN-1000/59/1A-H 120/S-cable lug- 36/187/P 15	MT-1000/60/1A-H 125/S-E40- 76/340/P 60	ME-1000/39/2B-H 120/S-E40- 165/380/H 45
Lamp wattage	W	1000	1000	1000	1000
Lamp voltage	V	120	120	130	130
Ignition voltage min./max.	kVs	4/5	4/5	4/5	4/5
Lamp current	A	9.6	9.6	9.5	9.5
Nominal luminous flux	lm	90000	90000	80000	100000
Luminous efficacy	lm/W	90	90	80	100
Average luminance	cd/cm ²	–	2600	810	23
Light colour/Colour appearance		NDL	D	D	N
Colour temperature	K	4400	5900	6000	3750
Colour rendering index	R _a	≥ 85	≥ 90	90	65
NIOSH	h	> 15 min	> 5.5 min	> 25	> 15
ACGIH UV output	mW	< 34	< 92	< 0.33	< 0.56
Base		cab cable	cab cable	E40	E40
Diameter d	mm	36	36	76	165
Length max. l	mm	187	187	340	380
LCL a	mm	93	93	220	–
Burning position		p 15	p 15	p 60	h 45
Average lamp life	h	6000	6000	9000	9000
Max. perm. outer bulb temp.	°C	950	950	550	400
Max. perm. base edge temp.	°C	390	390	250	250
PF corr. cap. at 50 Hz	µF	85	85	85	85
Lamp reference		HQI-TS 1000/NDL/S	HQI-TS 1000/D/S	HQI-T 1000/D	HQI-E 1000/N
EAN 4050300		349916	300092	015323	015279
Standard pack	Qty	10	10	6	6
Figure	No.	1	1	2	3
Circuit (see page 28)	Fig. no.	2	2	2	2







POWERSTAR® HQI®




HQI 2000 W

		D	T	T
		TS		T
		/S		/I
Type				
ILCOS		MN-2000/58/1A-E	MT-2000/60/1A-E	MT-2000/60/1A-E
		205/S-cable lug-36/187/P 15	230/I-E40-100/430/P 60	230/I-E40-100/430/P 60
Lamp wattage	W	1950	2000	2000
Lamp voltage	V	205	230	230
Ignition voltage min./max.	kVs	4/5	4/5	not reqd.
Lamp current	A	11.3 ¹⁾	10.3	10.3
Nominal luminous flux	lm	200000	180000	180000
Luminous efficacy	lm/W	100	90	90
Average luminance	cd/cm ²	7000	920	920
Light colour/Colour appearance		D	D	D
Colour temperature	K	5800	6000	6000
Colour rendering index	R _a	≥ 90	90	90
NIOSH	h	> 15 min	> 56	> 42
ACGIH UV output	mW	< 33	< 0.15	< 0.2
Base		cab	E40	E40
Diameter d	mm	36	100	100
Length max. l	mm	187	430	430
LCL a	mm	93	265	265
Burning position		p 15	p 60	p 60
Average lamp life	h	4000	9000	9000
Max. perm. outer bulb temp.	°C	950	550	500
Max. perm. base edge temp.	°C	390	250	250
PF corr. cap. at 50 Hz	µF	60	60	60
Lamp reference		HQI-TS 2000/D/S	HQI-T 2000/D	HQI-T 2000/D/I
EAN 4050300		271682	015330	015446
Standard pack	Qty	10	4	4
Figure	No.	1	2	2
Circuit (see page 28)	Fig. no.	2/4	2	1







1) Lamps may only be operated on 10.3 A chokes

POWERSTAR® HQI®



HQI 2000 W

		N	T	T	T	T
		TS /L	/E Super	/SN Super	/230 V	/without igniter
Type						
ILCOS		MN-2000/42/2B-E 234/S-cable lug- 32/275/P 15	MT-2000/40/2B-E 220/S-E40-	MT-2000/40/2B-E 220/E-E40-	MT-2000/45/2B-E 230/S-E40-	MT-2000/45/2B-E 220/S-E40-
Lamp wattage	W	2100	2000	2000	2000	2000
Lamp voltage	V	220	220	220	120	245
Ignition voltage min./max.	kVs	4/5	4/5	0.9/1.3	4/5	not reqd.
Lamp current	A	10.7	8.8	8.8	16.5	8.8
Nominal luminous flux	lm	225000	240000	240000	190000	200000
Luminous efficacy	lm/W	107	120	120	95	100
Average luminance	cd/cm ²	530	800	800	530	530
Light colour/Colour appearance		N	N	N	N	N
Colour temperature	K	4100	4000	4000	4400	4500
Colour rendering index	R _a	≥ 62	65	65	65	65
NIOSH	h	> 3.4 min	–	–	–	–
ACGIH UV output	mW	< 148	–	–	–	–
Base		cable	E40	E40	E40	E40
Diameter d	mm	32	100	100	100	100
Length max. l	mm	268	430	430	430	430
LCL a	mm	134	265	265	265	265
Burning position		p 15	p 30	p 30	p 30	universal ¹⁾
Average lamp life	h	6000	9000	9000	9000	9000
Max. perm. outer bulb temp.	°C	950	500	500	500	500
Max. perm. base edge temp.	°C	390	250	250	250	250
PF corr. cap. at 50 Hz	µF	60	37	37	125	37
Lamp reference		HQI-TS 2000/N/L	HQI-T 2000/N/E SUPER	HQI-T 2000/N/SN SUPER	HQI-T 2000/N/230 V	HQI-T 2000/N
EAN 4050300		607344	301860	348629	421582	015347
Standard pack	Qty	10	4	4	4	4
Figure	No.	1	2	2	2	2
Circuit (see page 28)	Fig. no.	2/4	2	2	2	1



1) p 30 recommended

Please note:

The values and curves published in this document are for guidance only. The basic data was determined under controlled laboratory conditions for a switching cycle of 11 h on/1 h off.

There may be considerable differences in actual practice. The highlighted areas around the curves represent a 90% confidence range based on our test conditions.

NIOSH threshold and ACGIH UV output:

The radiated energy of a lamp is indicated by the defined NIOSH curve.

The NIOSH effective radiated output calculated from this is converted into permitted exposure times with defined limit values.

The ACGIH UV output value correlates directly with the NIOSH value and represents the current required value for UV exposure.

PF correction capacitor:

The pf correction capacitors are designed so that $\cos \varphi \geq 0.9$ is achieved at rated voltage.

Operating instructions

Supply voltage:

The lamps must be connected via suitable control gear. A 240 V / 50 Hz ac supply is generally required. If a different supply voltage is used (e.g. 400 V / 50 Hz) control gear with appropriate taps must be used.

Permitted mains voltage deviation: $\pm 3\%$

Sudden fluctuations in mains voltage of more than 10% may cause the lamps to go out. If the deviation from rated supply voltage (230 V or 400 V) is permanent, high-pressure discharge lamps may exhibit changes in colour or luminous flux. Lamp life may also be reduced.

Control gear:

Conventional control gear: Choke, igniter and pf correction capacitor.

The right igniter for the particular lamp type must be used to ensure reliable and safe ignition. Igniters must always be installed close to the lamp. The choke may be installed any distance from the lamp, provided the permissible voltage drop is not exceeded.

For power supplies with a neutral conductor the choke should be connected to the live conductor. In the case of luminaires in which there are no lamps installed, the ignition equipment (igniter, ignition pulser) must be disabled when voltage is applied otherwise the igniters may produce radio interference.

The chokes and pf correction capacitors generally needed for operating discharge lamps may, under certain conditions, create oscillating circuits. These circuits may then produce excessive currents and voltages, which in turn can destroy the lamps, ballasts and capacitors. Such resonance phenomena must be avoided by appropriate circuits and fuses.

When high-pressure discharge lamps come to the end of their lives a rectifier effect may occur (see IEC 62035). This is not manufacturer-specific. Because of the excessive dc current components the ballasts and igniters may become overheated. High-pressure discharge lamps should therefore only be operated with control gear with thermal protection. This applies also to control gear with the option of power reduction.

The following lamps with integrated igniters will start on mains voltage:

- HQI®-T 2000 /D/I
- HQI®-T 2000 /N

The lamps must not be operated with integrated igniters in luminaires equipped with igniters.

Suitable igniters and control gear for POWERSTAR® and POWERBALL® are available from the electrical industry.

In the case of igniters equipped with OSRAM switching element SE 600 (built-in spark gap), SE 600 must be replaced each time the lamp is replaced.

Operating temperatures:

Only high-pressure discharge lamps with external igniters are suitable for low-temperature applications down to $-50\text{ }^{\circ}\text{C}$. Such applications call for special (heatable) igniters such as MZN 400 SU-LT from BAG Turgi (for lamps from 100 to 400 W).

Power factor:

CCG: Because of the series connected choke this is around 0.5 to 0.7 (without compensation)
ECG: If **POWERTRONIC®** is used the power factor is greater than 0.96. Compensation is therefore not needed here.

Switching on:

Full luminous flux is reached only a few minutes after the lamp is switched on. The start-up current may be up to twice the operating current depending on the control gear. (See also the graphs on p. 27)

Fusing:

HCI® and HQI® lamps must be protected by slow acting fuses. If fuse wire is used it is sufficient for it to be rated at twice the rated current of the lamp. If automatic cutouts are used they should have characteristic "C". If adjusted to the upper limit value of 10 x rated current there will be no triggering if fuse protection is at twice the rated lamp current.

Restarting:

The lamps will restart only after they have cooled down for 2 to 15 minutes.

For POWERSTAR® HQI®-TS = 1000 W and HQI®-TS 2000 /D/S, instant restarting is possible with suitable igniters. The necessary surge voltage is 25 to 60 KV_s.

Lampholders:

Because of the high voltages involved in ignition the lampholders must be designed for these high voltages. Lampholders that meet these requirements are available from appropriate manufacturers.

Power reduction:

Dimming metal halide lamps is not recommended. **OSRAM cannot provide a guarantee for dimmed lamps.** Dimming adversely affects colour rendering. The colour location shifts towards colder light colours and the colour spread increases. Dimmed lamps also tend to flicker. Luminous flux maintenance is significantly worse as a result of dimming. Dimming can shorten the life of the lamps.

End of life:

To protect the control gear and to avoid radio interference, high-pressure discharge lamps must be replaced as soon as they come to the end of their life.

These lamps reach their end of life when

- the light colour of the lamp changes dramatically
- there is a significant loss of brightness
- the lamp no longer ignites
- the lamp starts to cycle (periodically goes out and ignites again).

Notes on disposal:

All metal halide lamps contain small quantities of mercury. If they break, poisonous mercury vapour may be released. The lamps must be treated as waste requiring special supervision with EEC code **20 01 21*** for waste or residue containing mercury and should be passed to a relevant collection or recycling company.

Guarantee:

A guarantee can only be made if suitable control gear is used and the defined operating conditions are met.

Safety:

OSRAM high-pressure lamps meet the safety requirements defined in IEC 62035.

All HQI/HCI lamps up to 400 W are of UV-reduced design. The only exception at present in the HQI-TS 400 W. The lamp packaging will indicate this fact until there is any change.

Because of their high operating pressure the following lamps may only be used in fully enclosed luminaires designed to take them:

- All HCI®-TS and HQI®-TS
- All HCI®-T, all HCI®-TT and HQI®-T
- All HCI®-TC
- All HCI®-E ≥ 250 W and HQI®-E ≥ 250 W

As we cannot completely rule out the possibility of the bulb bursting, luminaires for the lamps mentioned above must be equipped with sealed shatter-proof shields that can withstand wide fluctuations in temperature.

Operating lamps with a damaged outer bulb is dangerous and therefore not permitted. Exception: HQI®-TS ... without an outer bulb.

Lamp operation:

Operating high-pressure lamps for short periods in combination with frequent on/off switching will shorten their life. This applies to both cold starting and hot restarts. The lamps should be operated for at least 3 hours and should remain off for at least 30 minutes. This applies in particular to HQI® = 1000 W.

The following lamps **are suitable for open luminaires:**

- All HQI®-E 70 W to 150 W
- All HQI®-E/P and HCI®-E/P

The use of shields should be considered for safety reasons in each case.

Luminaire design:

Luminaire design (thermal design and fuse protection) should be based on the EN 60598-1 standard.

HQI® 1000 W to 2000 W lamps should be held without pressure or by means of a lamp support close to the base-free end.

Photometric and electrical data:

All lamp-specific electrical and photometric data is measured after 100 hours of operation under laboratory conditions on reference equipment.

Unless otherwise indicated, the data relates to the horizontal burning position for T and TS types and to the base up burning position for E types. If different burning positions are used in actual practice there may be considerable changes in the lamp data, particularly with regard to luminous flux, colour temperature and lamp life.

The luminous flux is virtually unaffected by the ambient temperature outside the luminaire. At low ambient temperatures down to around -50 °C special igniters are needed.

Detailed information on heat accumulation tubes (luminaire simulators) for determining lamp data for HQI®-TS and HCI®-TS is given in DIN 5032, Part 2, Section 3.3.3.3.

Colour deviations:

With all metal halide lamps there may be differences in colour from one lamp to the next due to external factors such as mains voltage, type of control gear used, burning position and luminaire design.

Lamp life

There are a confusing number of definitions for lamp life, and these differ from one region to the next and from one application to the next. The basic definitions for the most common types are given below.

This document refers explicitly only to the **average life**.

Average life:

Average number of hours burned over several groups in which in the group in question half the lamps have failed as the result of a defect (50% failure).

Minimum life:

Minimum period of time in which a lamp remains in operation under laboratory conditions.


Economical life:

Period of time between group relamping of an installation under the condition that operating costs are minimised and the installation luminous flux does not fall below a particular value. This will vary according to the application.




Service life:

Simplified practical view of the economical life. This is the operating time after which the installation luminous flux (the product of the relative luminous flux and the lamps still in operation) is still around 70% (sometimes 80%).


Operating characteristics in relation to the supply voltage



Start-up behaviour (average value)



Circuit diagrams



B = 6A fuse, slow acting
D = Choke
K = PF correction capacitor
K+S = Time-limiting switch and contactor
L = Lamp
L_H = High-voltage terminal
Mp = Neutral conductor
Sch = Switch


U_N = 230 V ac mains voltage (for 2000 W = 400 V ac)
Z = Igniter to be installed near the lamp
ZL = HF igniter lead to contact plate of lamp

For power supplies with a neutral conductor the choke should be connected to the live conductor.


The right igniter for the particular lamp type must be used to ensure reliable and safe ignition.

Chokes, holder, capacitors and igniters are available from electrical suppliers.

Burning positions



Base




Spectral power distribution of discharge lamps

Visible range from 380 to 780 nm


Vertical scale $\frac{400 \text{ mW}}{1000 \text{ lm} \cdot 10 \text{ nm}}$

POWERBALL®


POWERSTAR®




HCl® .../WDL




HCl® .../NDL




HQI® .../WDL



HQI® .../NDL



HQI® .../N



HQI® .../D

Head office Germany

OSRAM GmbH
Hellabrunner Strasse 1
81536 München
Tel.: +49-89-62 13-0
Fax: +49-89-62 13-20 20

International addresses

Albania

(supported by OSRAM Greece)

Argentina

OSRAM Argentina S.A.C.I.
Ramos Mejia 2456
B 1643 ADN Beccar
Pcia. de Buenos Aires
Tel.: +54-11-6333-8000
Fax: +54-11-4737-0222

Australia

OSRAM Australia Pty. Limited
Building 1, 11th Floor
P.O. Box 673
423 Pennant Hills Road
Pennant Hills
2120 New South Wales
Tel.: +61-29-4 81-83 99
Fax: +61-29-4 81-94 68

Austria

OSRAM GmbH
Lemböckgasse 49/C/5
1230 Wien
Postfach 1 62
1231 Wien
Tel.: +43-1-6 80 68-0
Fax: +43-1-6 80 68-7

Baltic states:

Estonia, Latvia, Lithuania

(supported by OSRAM Finland)

Belgium

N.V. OSRAM S.A.
Mercuriusstraat 28
1930 Zaventem Zuid 7
Tel.: +32-2-7 19 29 11
Fax: +32-2-7 20 99 75

Bosnia-Herzegovina

(supported by OSRAM Croatia)

Brazil

OSRAM do Brasil Lâmpadas Elétricas Ltda.
Av. dos Autonomistas, 4229
06090-901 Osasco-SP
Tel.: +55-11-36 84 74 08
Fax: +55-11-36 85 94 95

Bulgaria

OSRAM EOOD
Nikola Obreschkov 1, Wh. A., App. 1
1113 Sofia / Bulgaria
Tel.: +359-2-9 71 22 62
Fax: +359-2-9 71 45 46

Canada

OSRAM SYLVANIA Ltd.
2001 Drew Road
Mississauga
Ontario L5S 1S4
Tel.: +1-905-6 73 61 71
Fax: +1-905-6 73 62 90

Chile

OSRAM Chile Ltda.
Santa Elena de Huechuraba
1135 B Huechuraba
Santiago-Chile
Tel.: +56-2-7 40-09 39
Fax: +56-2-7 40-04 66

China

OSRAM Foshan Lighting Co. Ltd.
No. 1 North Industrial Road,
Postal code 528000
Foshan, Guangdong, P.R. China
Tel.: +86-757-64 82-111
Fax: +86-757-64 82-222

OSRAM Shanghai Rep. Office
Harbour Ring Plaza No. 18
Xi Zang Middle Road
Room 2802, 2803 A
Shanghai, 200001 P.R.C.
Tel.: +86-21-53 85 28-48
Fax: +86-21-64 82 12-19

OSRAM Sylvania Inc.
PMC Shanghai Rep. Office
2805A 28/F Harbour Ring Plaza
No. 18 Xi Zang Rd. M. Shanghai
Shanghai, 200001 P.R.C.
Tel.: +86-21-53 85 28-48
Fax: +86-21-53 85 20 22

Colombia

OSRAM de Colombia
Diagonal 109 No. 21-05
Oficina 607, 608
Bogotá
Tel.: +57-1-6 19 24 07
Fax: +57-1-6 37 18 55

Croatia

OSRAM d.o.o.
Ozaljiska 93
10000 Zagreb
Tel.: +385-1-303-20 00
Fax: +385-1-303-20 01

Czech Republic

OSRAM spol. s.r.o. Praha
Tylovo náměstí 3/15
12000 Praha 2
Tel.: +420-2-2 19 87-100
Fax: +420-2-2 19 87-120

Denmark

OSRAM A/S
Dybendsalvaenget 3
Postboks 259
2630 Tåstrup
Tel.: +45-44-77 50-00
Fax: +45-44-77 50-55

Egypt

OSRAM Cairo
Rep. Office OSRAM GmbH
5th Floor, Unit No. 507
57 Giza Street
Cairo, Giza
Tel.: +20-2-7 48 66 46
Fax: +20-2-7 48 66 46

Ecuador

OSRAM del Ecuador S.A.
Casilla 09-01-8410
Guayaquil
Tel.: +593-4-2 89 36 09
Fax: +593-4-2 89 35 58

Finland

OSRAM Oy
Vanha Porvoontie 229
01380 Vantaa
Box 91
01301 Vantaa
Tel.: +358-9-74 22 33 00
Fax: +358-9-74 22 33 74

France

OSRAM S.A.
1, Rue d'Altorf
67120 Molsheim
BP 1 09
67124 Molsheim Cedex
Tel.: +33-388-49 75 99
Fax: +33-388-49 75 97

Great Britain

OSRAM Ltd.
OSRAM House
Waterside Drive
Langley, Berkshire
SL3 6EZ
Tel.: +44-17 44-81 22 21
Fax: +44-17 44-83 19 00

Greece

OSRAM A.E.
Athinon Av. 56
10441 Athen
Tel.: +30-210-5 20 18 00
Fax: +30-210-5 22 72 00

Hong Kong

OSRAM Prosperity Co. Ltd.
Rm 4007-09 Office Tower, Convention Plaza
1 Harbour Road, Wanchai
Hong Kong
Tel.: +852-25 11 22 68
Fax: +852-25 11 20 38

Hungary

OSRAM KFT.
Alkotás utca 41.
1123 Budapest
Pf.: 700/61
1535 Budapest
Tel.: +36-1-2 25-30 55
Fax: +36-1-2 25-30 54

Iceland

Jóhann Ólafsson & Co. hf/
43 Sundaborg 13
104 Reykjavik
Tel.: +354-533 19 00
Fax: +354-533 19 30

India

OSRAM India Ltd.
Signature Towers, 11th Floor,
Tower-B South City-I
122001 Gurgaon Haryana/India
Tel.: +91-124-238 31-80
Fax: +91-124-238 31-82

Indonesia

PT OSRAM Indonesia
Jalan Siliwangi KM 1
Desa Keroncong
Jatiuwung
15134 Tangerang
Tel.: +62-21-5 90 01 27-00
Fax: +62-21-5 90 05 59

Iran

OSRAM Lamp Private Joint Stock Company
(OSRAM PJS Co.)
Bokharest Ave, Str. 6, No. 13
Tehran
Iran
Tel.: +98-21-8 73 84 76
Fax: +98-21-8 73 24 13

Italy

OSRAM Società Riunite
OSRAM Edison-Clerici S.p.A.
Via Savona 105
Casella Postale 1 41 06
20144 Milano
Tel.: +39-02-42 49-1
Fax: +39-02-42 49-380

Japan

OSRAM-MELCO Ltd.
Tobu Yokohama Bldg.No. 3 (4F) 8-29,
Kitasaiwai 2-chome, Nishi-Ku
220-0004 Yokohama
Tel.: +81-45-3 23 51-20
Fax: +81-45-3 23 51-55

OSRAM Ltd.

Tobu Yokohama Bldg.No. 3 (6F) 8-29,
Kitasaiwai 2-chome, Nishi-Ku
220-0004 Yokohama
Tel.: +81-45-3 23 51-00
Fax: +81-45-3 23 51-10

Korea

OSRAM Korea Co., Ltd.
3rd. Fl. Ye-Sung Bldg. 150-30
Samsung-dong, Kangnam-Ku
Seoul 135-090
Tel.: +82-2-5 54 41 12
Fax: +82-2-5 56 16 44

Macedonia

(supported by OSRAM Greece)

Malaysia

OSRAM (Malaysia) Sdn Bhd
7.05-7.06 Amoda Building
22, Jalan Imbi
55100 Kuala Lumpur
Tel.: +60-3-21 45 95-33
Fax: +60-3-21 45 95-35

Mexico

OSRAM de México, S.A. de C.V.
Camino a Tepalcapa No. 8
54900 Tultitlán/Edo. de México
Tel.: +52-5-58 99-18 00
Fax: +52-5-58 99-65 60

Netherlands

OSRAM Nederland B.V.
Vennootsweg 15
2404 CG Alphen a/d Rijn
Postbus 3 32
2400 Alphen a/d Rijn
Tel.: +31-172-48 38 38
Fax: +31-172-44 30 25

Norway

OSRAM Oslo
OSRAM AS
Strandveien 50
N-1366 Lysaker
Tel.: +47-67 83 67-00
Fax: +47-67 83 67-40

Philippines

OSRAM Philippines
Unit 2002-2003
Antel Global Corporate Center
Julia Vargas Avenue
Ortigas Center
Pasig City
Tel.: +632-687 60 48-50
Fax: +632-687 60 57

Poland

OSRAM Sp. z o.o.
ul. Wiertnicza 117
PL 02292 Warszawa
Tel.: +48-22-6 51 78 69
Fax: +48-22-6 42 14 18

Portugal

OSRAM Empresa de
Aparelhagem Eléctrica Lda.
Rua Alto do
Montijo Nr. 15-4 andar
2795-619 Carnaxide
Tel.: +351-2 10 34-78 50
Fax: +351-2 10 34-78 51

Romania

OSRAM Romania S.R.L.
Sos. Pipera Nr. 41 Sector 2
7000 Romania/Bucaresti
Tel.: +40-21-2 33 02-12
Fax: +40-21-2 33 02-14

Russia

OSRAM RUS
Rep. Office OSRAM GmbH
Ul. Malaja Kaluschkaja 15/4
119071 Moscow
Tel.: +7-095-9 35 70-70
Fax: +7-095-9 35 70-76

Singapore

OSRAM Singapore (Pte.) Ltd.
159 Sin Ming Road
#05-04 Amtech Building
575625 Singapore
Tel.: +65-65 52 01 10
Fax: +65-65 52 71 17

Slovak Republic

OSRAM Slovakia a.s.
Komárňanská cesta 7
94093 Nové Zámky
Tel.: +42-1-35 64 64-409
Fax: +42-1-35 64 64-893

Slovenia

(supported by OSRAM Austria)

South Africa

OSRAM (Pty.) Ltd., Midrand
260, 15th Road
1685 Randjespark
Private BAG X 206
1683 Midrand
Tel.: +27-11-2 07 56 00
Fax: +27-11-8 05 17 11

Spain

OSRAM, S.A.
Calle de la Solana, 47
28850 Torrejón de Ardoz (Madrid)
Tel.: +34-91-6 55 52 00
Fax: +34-91-6 77 92 40

Sweden

OSRAM AB
Rudanvägen 1
Box 5 04
13625 Haninge
Tel.: +46-8-7 07 44-00
Fax: +46-8-7 07 44-40

Switzerland

OSRAM AG
In der Au 6
Postfach 2179
8401 Winterthur/Töss
Tel.: +41-52-2 09 91 91
Fax: +41-52-2 09 99 99

Taiwan

OSRAM Taiwan Company Ltd.
Sung Chiang Road, 7th Floor
Empire Building No. 87
P.O. Box 46304
Taipei
Tel.: +886-2-25 08 35 02
Fax: +886-2-25 09 67 82

Thailand

OSRAM Thailand Co., Ltd.
100/45, 24th Floor
Sathorn Nakorn Tower
North Sathorn Road
Khaeng Silom
Khet Bangrak, Bangkok 10500
Tel.: +66-2-6 36 74 75
Fax: +66-2-6 36 74 77

Turkey

OSRAM AMPUL TIC. A.S.
Meclisi Mebusan Caddesi 125
80400 Fındıklı Istanbul
Tel.: +90-212-334-1334
Fax: +90-212-334-1142

Ukraine

OSRAM Kiev
Rep. Office OSRAM GmbH
Ul. Vorovskogo, 36
01054 Kiev
Tel.: +380-44-2 46 93 14
Fax: +380-44-2 46 99 91

United Arab Emirates

OSRAM Middle East FZE
4th Floor, New High Rise Building
LOB 14
P.O. Box 17476
Jebel Ali, Dubai
Tel.: +971-4-88 13-767
Fax: +971-4-88 13-769

USA

OSRAM SYLVANIA INC.
100 Endicott Street
Danvers, MA 01923
Tel.: +1-978-777-19 00
Fax: +1-978-777-12 47

Vietnam

OSRAM Singapore Pte. Ltd.
Rep. Office Vietnam
59A Ly Thai To Street, Hanoi Press Club
Hoan Kiem District
Hanoi - Vietnam
Tel.: +84-4-93 49-801
Fax: +84-4-93 49-803

Yugoslavia

OSRAM Belgrad
Rep. Office of OSRAM GmbH
Predstavništvo OSRAM GmbH
Čika Ljubina 15/V
11000 Beograd
Tel.: +381-11-30 30-860
Fax: +381-11-30 30-853

Internet

<http://www.osram.de>
<http://www.osram.com>
<http://www.osram.de/lightatwork/>
<http://www.osram.com/lightatwork/>