

# Datasheet 30W High power LED Flood Light

**ENGLISH** 

RS Stock No.: 787-1317

#### **Features:**

45 mil Epistar chip

Beam Angle: 120°-140°

CE,RoHS,IP65 Certification

## **Specifications:**




Commodity	30W LED Flood light
Input Voltage	AC85-265V
Frequency Range	50~60Hz
Power Factor (PF)	> 0.9
Lamp's Efficiency (%)	> 90%
Led Power	30W
Led Luminous Efficiency	≥80-90 lm/w
Led Flux	≥2400-2700 lm/w
Beam Angle	120°-140°
Color Temperature	cool white
Color Temperature	6000-6500K
Color Index(CRI)	Ra > 80
Working Temperature	(-30℃) ~( 45℃)
IP Rating	IP65
Working Life	50000 hrs


RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.




#### **Dimensions:**

**ENGLISH** 







### **Applications:**

Floodlighting and wall washing light for bars, clubs, hotels, stages, parks, squares, commercial buildings facade, museums, and art galleries, historical buildings.





RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.