



1 2 3

LED PERFORMANCE PAR16

Product Name	GTIN (EAN)	w	W	lm	cd	K	Ra	2	°	l [mm]	d [mm]	t [h]	3	Light No.	
LED PERFORMANCE PAR16 HIGH BRIGHTNESS 110															
LP PAR16 24 10W/927 230V GU10	4058075415621	110	GU10	10	790	2,950	2,700	95	✓	24°	77.3	49.5	25,000	10	1
LP PAR16 24 10W/930 230V GU10	4058075415676	110	GU10	10	830	3,100	3,000	95	✓	24°	77.3	49.5	25,000	10	1
LP PAR16 24 10W/940 230V GU10	4058075415720	110	GU10	10	900	3,350	4,000	95	✓	24°	77.3	49.5	25,000	10	1
LP PAR16 36 10W/927 230V GU10	4058075415775	110	GU10	10	790	2,050	2,700	95	✓	36°	77.3	49.5	25,000	10	1
LP PAR16 36 10W/930 230V GU10	4058075415850	110	GU10	10	830	2,150	3,000	95	✓	36°	77.3	49.5	25,000	10	1
LP PAR16 36 10W/940 230V GU10	4058075415881	110	GU10	10	900	2,350	4,000	95	✓	36°	77.3	49.5	25,000	10	1
LED PERFORMANCE PAR16 80															
LP PAR16 80 36 7.5W/927 230V GU10	4058075414624	80	GU10	7.5	650	950	2,700	90	✓	36°	55	50	25,000	10	2
LP PAR16 80 36 7.5W/930 230V GU10	4058075414648	80	GU10	7.5	650	950	3,000	90	✓	36°	55	50	25,000	10	2
LP PAR16 80 36 7.5W/940 230V GU10	4058075414662	80	GU10	7.5	650	950	4,000	90	✓	36°	55	50	25,000	10	2
LP PAR16 80 36 7.5W/965 230V GU10	4058075417373	80	GU10	7.5	650	950	6,500	90	✓	36°	55	50	25,000	10	2
LED PERFORMANCE PAR16 50															
LP PAR16 50 24 5.5W/927 230V GU10	4058075165755	50	GU10	5.5	380	1,200	2,700	90	✓	24°	55	51	25,000	10	3
LP PAR16 50 36 5.5W/927 230V GU10	4058075165793	50	GU10	5.5	380	750	2,700	90	✓	36°	55	51	25,000	10	3
LP PAR16 50 36 5.5W/930 230V GU10	4058075332065	50	GU10	5.5	380	350	3,000	90	✓	36°	55	51	25,000	10	3
LP PAR16 50 36 5.5W/940 230V GU10	4058075332089	50	GU10	5.5	400	350	4,000	90	✓	36°	55	51	25,000	10	3
LP PAR16 50 36 5.5W/965 230V GU10	4058075332102	50	GU10	5.5	400	350	6,500	90	✓	36°	55	51	25,000	10	3

¹All technical parameters apply to the complete lamp. Due to the complex manufacturing process of light emitting diodes, the specified typical values of the LED parameters merely represent purely statistical variables. They do not necessarily correspond to the actual technical parameters of each individual product, which can deviate from the typical value
²LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there
³L70/B50

LEDVANCE is licensee of product trademark OSRAM for lamps products in general lighting.





1 2 3

LED VALUE PAR16

Product Name	GTIN (EAN)	w/w	mm	W ¹	lm ¹	cd	K	R _a	° ²	°	l [mm]	d [mm]	t [h] ³	Light Bulb No.
--------------	------------	-----	----	----------------	-----------------	----	---	----------------	----------------	---	--------	--------	--------------------	----------------

LED VALUE PAR16 80

CRI 80

LV PAR16 80 36 7.5W/827 230V GU10	4058075417397	80	GU10	7.5	650	1,000	2,700	80	–	36°	55	50	15,000	10	1
LV PAR16 80 36 7.5W/840 230V GU10	4058075417410	80	GU10	7.5	650	1,000	4,000	80	–	36°	55	50	15,000	10	1
LV PAR16 80 36 7.5W/865 230V GU10	4058075417434	80	GU10	7.5	650	1,000	6,500	80	–	36°	55	50	15,000	10	1
LV PAR16 80 36 7W/827 230V GU10	4058075166226	80	GU10	7	625	1,400	2,700	80	–	36°	52	50	15,000	10	2
LV PAR16 80 36 7W/840 230V GU10	4058075166240	80	GU10	7	625	1,400	4,000	80	–	36°	52	50	15,000	10	2
LV PAR16 80 36 7W/865 230V GU10	4058075166264	80	GU10	7	625	1,400	6,500	80	–	36°	52	50	15,000	10	2
LV PAR16 80 60 7W/830 230V GU10	4058075187474	80	GU10	7	625	700	3,000	80	–	60°	52	50	15,000	10	2

LED VALUE PAR16 50

CRI 80

LV PAR16 50 36 4.5W/827 230V GU10	4058075168343	50	GU10	4.5	380	750	2,700	80	–	36°	55	51	15,000	10	2
LV PAR16 50 36 4.5W/840 230V GU10	4058075168367	50	GU10	4.5	400	750	4,000	80	–	36°	55	51	15,000	10	2
LV PAR16 50 36 4.5W/865 230V GU10	4058075168381	50	GU10	4.5	420	750	6,500	80	–	36°	55	51	15,000	10	2
LV PAR16 50 24 4.5W/827 230V GU10	4058075168404	50	GU10	4.5	380	1,200	2,700	80	–	24°	55	51	15,000	10	2

LED ECO PAR16

Product Name	GTIN (EAN)	w/w	mm	W ¹	lm ¹	cd	K	R _a	° ²	°	l [mm]	d [mm]	t [h] ³	Light Bulb No.
--------------	------------	-----	----	----------------	-----------------	----	---	----------------	----------------	---	--------	--------	--------------------	----------------

LED ECO PAR16 50

CRI 80

LE PAR16 50 36 4W/830 230V GU10	4058075204553	50	GU10	4	350	750	3,000	80	–	36°	52	50	8,000	10	3
LE PAR16 50 36 4W/840 230V GU10	4058075204577	50	GU10	4	350	750	4,000	80	–	36°	52	50	8,000	10	3
LE PAR16 50 36 4W/865 230V GU10	4058075204591	50	GU10	4	350	750	6,500	80	–	36°	52	50	8,000	10	3

LED ECO PAR16 35

CRI 80

LE PAR16 35 36 2.5W/830 230V GU10	4058075204515	35	GU10	2.5	220	400	3,000	80	–	36°	52	50	8,000	10	3
LE PAR16 35 36 2.5W/865 230V GU10	4058075204539	35	GU10	2.5	220	400	6,500	80	–	36°	52	50	8,000	10	3

¹ All technical parameters apply to the complete lamp. Due to the complex manufacturing process of light emitting diodes, the specified typical values of the LED parameters merely represent purely statistical variables. They do not necessarily correspond to the actual technical parameters of each individual product, which can deviate from the typical value

² LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there

³ L70/B50