



Essential SmartBright G3 LED Floodlight

BVP150 LED17/WW 220-240V 20W SWB CE

Essential SmartBright G3 LED Floodlight - 1700 lm - 20 W - 3000 K

The Essential SmartBright G3 LED floodlight comes with a compact and sturdy design. Its light weight with robust die-cast aluminum housing and corrosion-proof coating, suitable for general outdoor application. Higher efficacy than last generation, achieves more energy savings.

Product data

General Information		Serviceability class	
Light source color	830 warm white	Serviceability class	Class C, luminaire without serviceable parts, not serviceable
Light source replaceable	No	Light Technical	
Driver included	Yes	Standard tilt angle posttop	-
Optical cover/lens type	Glass bowl/cover	Standard tilt angle side entry	-
Luminaire light beam spread	110°	Operating and Electrical	
Control interface	-	Input Voltage	220 to 240 V
Connection	Flying leads/wires	Input Frequency	50 to 60 Hz
Cable	Cable 0.3 m without plug	Inrush current	0.778 A
Protection class IEC	Safety class I	Inrush time	0.0083 ms
Flammability mark	For mounting on normally flammable surfaces	Power Factor (Min)	0.9
CE mark	CE mark	Controls and Dimming	
Optic type outdoor	Symmetrical wide beam	Dimmable	No
Constant light output	No		
Number of products on MCB of 16 A type B	112		
Light source engine type	LED		

Essential SmartBright G3 LED Floodlight

Mechanical and Housing

Housing Material	Aluminum die cast
Optical cover/lens material	Glass
Fixation material	Steel
Mounting device	Mounting bracket adjustable
Optical cover/lens shape	Flat
Optical cover/lens finish	Textured
Overall length	140 mm
Overall width	110 mm
Overall height	28 mm
Color	Black

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Surge Protection (Common/Differential)	Surge protection level until 2 kV

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	1700 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	85 lm/W

Init. Corr. Color Temperature	3000 K
Init. Color Rendering Index	>80
Initial chromaticity	SDCM<7
Initial input power	20 W
Power consumption tolerance	+/-10%

Application Conditions

Ambient temperature range	-40 to +50 °C
---------------------------	---------------


Product Data

Full product code	871016333014399
Order product name	BVP150 LED17/WW 220-240V 20W SWB CE
EAN/UPC - Product	8710163330143
Order code	911401732352
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	911401732352
Net Weight (Piece)	0.318 kg



Dimensional drawing

20W



BVP150/161 Essential Smartbright LED

