

CorePro LEDbulb

CorePro LEDbulb ND 5-40W A60 E27 840

CorePro LEDbulbs are compatible with existing fixtures with an E27 or B22 holder and are designed for retrofit replacement of incandescent bulbs. They deliver huge energy savings and minimize maintenance cost.

Product data

• General Information

Cap-Base Bulb Shape Nominal Lifetime (Nom) Switching Cycle B50L70 Technical Type

• Light Technical

Color Code Beam Angle (Nom) Luminous Flux (Nom) Luminous Flux (Rated) (Nom) Color Designation Rated Beam Angle Correlated Color Temperature (Nom) Luminous Efficacy (rated) (Nom) Color Consistency Color Rendering Index (Nom) LLMF At End Of Nominal Lifetime (Nom)

• Operating and Electrical

Power (Rated)	5 W
(Nom)	
Lamp Current (Nom)	55 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s

E27 [E27] A60 [A 60mm] 15000 h

50000X 15000 5-40VV

840 [CCT of 4000K (841)] 200 ° 470 lm 470 lm Cool White (CW) 200 ° 4000 K 94.00 lm/W <6 80 70 %

Warm Up Time To 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.5
Voltage (Nom)	220-240 V

- Temperature T-Case Maximum 84 °C (Nom)
- Controls and Dimming
 Dimmable
 No
- Mechanical and Housing Bulb Finish Frosted
- Approval and Application

Energy Saving Yes Product Suitable For Accent No Lighting Energy Efficiency A+ Label (EEL) Energy Consumption 5 kWh kWh/1000 h

• Product Data

Full product code Order product name

> EAN/UPC - Product Order code


871869657779000 CorePro LEDbulb ND 5-40W A60 E27 840 8718696577790 929001234602



CorePro LEDbulb

Numerator - Quan-	1
tity Per Pack	
Numerator - Packs	10
per outer box	

Dimensional drawing




Material Nr. (12NC) Net Weight (Piece)

929001234602 0.076 kg

Entrybulb 230V 6W-40W 470Im 4000K E27 ND

Product	D	С
CorePro LEDbulb ND 5-40W A60 E27 840	60 mm	110 mm

Photometric data





© 2016 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting