



CorePro LEDlinear MV

CorePro LED linear D 14-120W R7S 118 830

CorePro R7S is a retrofit replacement for traditional double-ended linear R7S lamps. Its 'light all around' design delivers light just like a halogen lamp. Within the range you can choose dimmable products which have deep dimming function that enables a cozy ambience when using a dimmable fixture.

Product data

General Information	
Cap-Base	R7S [R7s]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	15000 h
Switching Cycle	50000X
Technical Type	14-120W

Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux (Nom)	2000 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	142.86 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Nom)	14 W
Lamp Current (Nom)	75 mA
Wattage Equivalent	120 W
Starting Time (Nom)	0.5 s

Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.8
Voltage (Nom)	220-240 V

Temperature	
T-Case Maximum (Nom)	100 °C

Controls and Dimming	
Dimmable	Yes

Approval and Application	
Energy Efficiency Label (EEL)	A++
Energy Consumption kWh/1000 h	14 kWh

Product Data	
Full product code	871869671400300
Order product name	CorePro LED linear D 14-120W R7S 118 830
EAN/UPC - Product	8718696714003
Order code	929001353602
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001353602
Net Weight (Piece)	0.095 kg

CorePro LEDlinear MV


Dimensional drawing

C


Product	D	C
CorePro LED linear D 14-120W R7S 118 830	29 mm	118 mm

R7S 220V 15.5W-110W 1800lm 3000K R7S D

Photometric data




General Lighting Catalogue Page 117



CorePro LEDlinearMV 14-120W R7S 830 D


CorePro LEDlinearMV 14-120W R7S 830 D




CorePro LEDlinearMV 14-120W R7S 830 D

CorePro LEDlinear MV

Lifetime



LEDbulb 60W E14 827 FR B38



LEDbulb 60W E14 827 FR B38

