

CorePro LEDlinear MV

CorePro LED linear D 14-120W R7S 118 840

CorePro R7S is a retrofit replacement for traditional double-ended linear R7S lamps. Its 'light all around' design delivers light just like a halogen lamp. Within the range you can choose dimmable products which have deep dimming function that enables a cozy ambience when using a dimmable fixture.

Product data

General Information	
Cap-Base	R7S [R7s]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	15000 h
Switching Cycle	50000X
Technical Type	14-120W
Light Technical	
Color Code	840 [CCT of 4000K]
Luminous Flux (Nom)	2000 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	142.86 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Nom)	14 W
Lamp Current (Nom)	75 mA
Wattage Equivalent	120 W
Starting Time (Nom)	0.5 s

Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.8
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	100 °C
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Energy Efficiency Label (EEL)	A++
Energy Consumption kWh/1000 h	14 kWh
Product Data	
Full product code	871869671406500
Order product name	CorePro LED linear D 14-120W R7S 118 840
EAN/UPC - Product	8718696714065
Order code	929001353702
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001353702
Net Weight (Piece)	0.095 kg

CorePro LEDlinear MV



Dimensional drawing

C

Product	D	C
CorePro LED linear D 14-120W R7S 118 840	29 mm	118 mm


R7S 220V 15.5W-120W 2000lm 4000K R7S D

Photometric data



NAM Highbay 165W EX39 4000K 60-120D NB WB UDL


CorePro LEDlinearMV 14-120W R7S 840 D




CorePro LEDlinearMV 14-120W R7S 830 D

CorePro LEDlinear MV

Lifetime



LEDbulb 60W E14 827 FR B38



LEDbulb 60W E14 827 FR B38

