

Essential SmartBright LED Downlight

DN020B G3 LED4/NW 4.5W 220-240V D90 SNI

Essential SmartBright G2 LED Downlight is value for money product with high efficacy, good quality and reliability. It offers multiple configurations from 300lm to 2000lm output, to replace conventional downlight. It can be used for shopping mall, retail store, residential and office. It's an ideal product family to distribute in trade market.

Product data

General information	
Light source color	840 neutral white
Light source replaceable	No
Luminaire light beam spread	110°
Connection	Flying leads/wires
Protection class IEC	Safety class II
Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.45
Controls and dimming	
Dimmable	No
Mechanical and housing	
Housing Material	Plastic
Reflector material	Polycarbonate
Optic material	Polycarbonate
Fixation material	Steel

Optical cover/lens finish	Opal
Overall length	115 mm
Overall width	115 mm
Overall height	35 mm
Overall diameter	105 mm
Color	White
Dimensions (Height x Width x Depth)	35 x 115 x 115 mm
Approval and application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK03 [0.3 J]
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	400 lm
Initial LED luminaire efficacy	88.00 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	80
Initial chromaticity	(0.3818, 0.3797) 6
Initial input power	4.5 W


Essential SmartBright LED Downlight

Power consumption tolerance	+/-10%
Over time performance (IEC compliant)	
Driver failure rate at 5000 h	1.6 %
Median useful life L70B50	20000 h
Application conditions	
Ambient temperature range	-20 to +40 °C
Product data	
Full product code	871869977961000

Order product name	DN020B G3 LED4/NW 4.5W 220-240V D90 SNI
EAN/UPC - Product	8718699779610
Order code	929002511317
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	929002511317
Net Weight (Piece)	0.061 kg





Dimensional drawing



DN020B G3 LED4/NW 4.5W 220-240V D90 SNI

Photometric data




Downlight DN020 G3 NW 4,5W D90 SNI


Downlight DN020 G3 NW 4,5W D90 SNI

Essential SmartBright LED Downlight

Lifetime



L70B50 20K-LMP



L70B50 20K-LED

