

ToLEDo GLS

ToLEDo GLS V6 1055LM 827 B22 SL

0026689



Product features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent GLS lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- A+ energy rating



PRODUCT OVERVIEW

IPC Code	0026689
Product name	ToLEDo GLS V6 1055LM 827 B22 SL
Technology	LED
Watt (Rated) (W)	11
Cap/Base	B22
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
Luminous flux (lm)	1055
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Wattage (W)	11
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288266893

DATA TABLE

General data

IPC Code	0026689
Product name	ToLEDo GLS V6 1055LM 827 B22 SL
Technology	LED
Watt (Rated) (W)	11
Cap/Base	B22
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959

Optical data

Luminous flux (lm)	1055
Luminous flux (Rated) (lm)	1055
Colour temperature (K)	2700

ToLEDo GLS

ToLEDo GLS V6 1055LM 827 B22 SL

0026689

Light colour	Homelight
CRI (Ra)	80
Beam angle (Rated) (°)	180
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	11
Equivalent watt (W)	75
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Inrush Current (A)	3.3
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	11
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	120
Max. Luminaires per 16A C Breaker	201
Max. Luminaires per 20A C Breaker	252

Lifetime data

Performance ambient temperature Tq (°C)	25
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	118
Nominal Product Diameter (mm)	60
Weight (kg)	0.053

Packaging

Single packaging type	Carton
Product EAN number	5410288266893
Packaging single length / height (cm)	11.3
Packaging single width (cm)	6.4
Packaging single depth (cm)	6.4
DUN14 (outer)	15410288266890
Units per inner package	6
Packaging inner length / height (cm)	20.4
Packaging inner width (cm)	13.4
Packaging inner depth (cm)	13.7
DUN14 (inner)	25410288266897
Units per outer package	60
Packaging outer length / height (cm)	72.4
Packaging outer width (cm)	22.2

ToLEDo GLS

ToLEDo GLS V6 1055LM 827 B22 SL

0026689

Packaging outer depth (cm)	29.7
----------------------------	------

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

