



## AZPOSE LED Floodlight XL2 / XL2S series

LED  
PRO

The AZPOSE XL2 is a LED floodlight fixture with optional built-in microwave sensor and comes with a remote control. It is an environmental-friendly lighting which saves up to 80% energy compared to conventional floodlights. With the built-in microwave sensor, AZPOSE XL2 can toggle between 100% and 0% brightness which further reduces the power consumption. The adjustable daylight sensor determines when the floodlight should be activated and can be programmed to operate during low light level.

### Superb Performance

- Energy-efficient LED light source provides higher brightness
- Saves up to 80% energy compared to conventional floodlights
- IP65 compliant rugged casing suitable for outdoor applications
- Maintenance-free for lifespan of 35,000 hours



### Flexibility



- Separate pan and tilt adjustment gives maximum flexibility for illumination
- Adjustable duration for illumination: 5/10/30 sec /1/5/15 mins
- Adjustable operating mode: Daytime/Dust/Night

### Microwave Sensor

- Built-in microwave motion sensor to provide sensing
- Microwave sensor detection angle: 30-150°
- Microwave induction sensitivity: high/medium/low sensitivity control
- Low standby power of <math><0.5W</math>

### Applications

- Commercial lighting
- Outdoor lighting – walkway, car porch, garden etc

Model No.	XL2-1515	XL2S-1515 	XL2-3030	XL2S-3030 
-----------	----------	---------------------------------------------------------------------------------------------	----------	-----------------------------------------------------------------------------------------------

**Electrical Data**

Wattage	15W	30W
Voltage	100–240V~, 50/60Hz	
Power Factor	>0.9	

**Photometric Data**

Luminous Flux	1500lm	3000lm
Light Colour	Warm white / Cool white / Day light	
Colour Temperature	3000K / 4000K / 6500K	
CRI	80	

**Microwave Sensor**

Detection Zone	–	Max. 9m	–	Max. 9m
Detection Angle	–	30°–150°	–	30°–150°
Hold-Time	–	5 / 10 / 30 sec 1 / 5 / 15 mins	–	5 / 10 / 30 sec 1 / 5 / 15 mins

**Performance**

Lifspan	35,000 hours	
Alternative for	70W HID Floodlight	150W HID Floodlight
Certified	  	

**Dimensions**

Weight	1.63kg	1.99kg
Size	235(L) x 210(W) x 164(H) mm	235(L) x 210(W) x 202(H) mm

**Line Drawing**

