

Product datasheet

Specifications



AvatarOn, 2 USB charger + switched socket, 3P, 13A, White

E8315USB_WE_G2

Main

| | |
|---------------------------|-------------------------------|
| Product or component type | USB charger + switched socket |
| Fixing mode | By screws |

Complementary

| | |
|---------------------------------------|--|
| Outlet standard | British |
| Outlet standard description | With earthing contact |
| Integrated connection type | 2 USB type A 5 V DC 2.1 A 1 socket-outlet 250 V AC 13 A 50/60 Hz |
| Device mounting | Surface |
| Device presentation | Complete product |
| Mounting support | Mounting box |
| Outlet poles configuration | 3P with shutter |
| Colour tint | White |
| Surface finish | Matt |
| Surface treatment | Untreated |
| Type of packing | Flow-pack |
| Quantity per set | Set of 10 |
| Ambient air temperature for storage | -5...60 °C |
| Protection type | Current protection Thermal protection |
| Dielectric strength | 2000 V |
| Ambient air temperature for operation | 0...40 °C |
| Service life in cycles | 5000 cycles |
| Connections - terminals | Screw terminal |
| Number of terminals | 3 |
| Screwdriver shape | Phillips combined |
| Number of cables | 2 |
| Clamping connection capacity | 1.5...4 mm ² for rigid cable(s) 1.5...4 mm ² for stranded cable(s) 1.5...4 mm ² for flexible cable(s) |

| | |
|------------------------------|--|
| Material | PC (polycarbonate): grid plate PC (polycarbonate): surround |
| Wire stripping length | 12 mm |
| Height | 86 mm |
| Width | 86 mm |
| Depth | 38.2 mm |
| Embedding depth | 29.3 mm |
| Standards | UL 498 UL 94 UL 1310 |

Environment

| | |
|--------------------------------|------|
| IP degree of protection | IP20 |
|--------------------------------|------|

Packing Units

| | |
|-------------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 109.0 g |
| Package 1 Height | 3.4 cm |
| Package 1 Width | 8.6 cm |
| Package 1 Length | 8.6 cm |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Weight | 1.09 kg |
| Package 2 Height | 9.5 cm |
| Package 2 Width | 19.0 cm |
| Package 2 Length | 19.5 cm |
| Unit Type of Package 3 | CAR |
| Number of Units in Package 3 | 60 |
| Package 3 Weight | 6.54 kg |
| Package 3 Height | 21.0 cm |
| Package 3 Width | 30.0 cm |
| Package 3 Length | 39.5 cm |

Offer Sustainability

| | |
|-----------------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |