

AvatarOn, switch, 16AX, 250V, 1 way, Metal Gold Hairline

E8331L1_GH_G2

Main

Product or component type	Switch
Device application	Control
Load type	Resistive Fluorescent lamp Inductive Incandescent lamp
Colour tint	Metal gold hairline

Complementary

Device presentation	Complete product
Rated current	16 AX at 250 V AC 50/60 Hz
Switch function	1-pole 1-way
Number of gangs	1 gang
Number of rocker	1
Clamping connection capacity	3 x 2.5 mm² for solid cable(s) 3 x 2.5 mm² for stranded cable(s) 4 x 1.5 mm² for solid cable(s) 4 x 1.5 mm² for stranded cable(s)
Connections - terminals	Brass terminal
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame Polycarbonate + GF 20 %: actuator
Device mounting	Flush Surface
Width	86 mm
Height	86 mm
Depth	34.2 mm

Environment

IP degree of protection	IP20
Maximum ambient air temperature for operation	45 °C
Operating altitude	2000 m
Relative humidity	095 %

Environmental characteristic	UV resistant	
Standards	MS IEC 60669-1 SS 227-1 BS EN 60669-1 IEC 60669-1 IS 3854	
Packing Units		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	77.0 g	
Package 1 Height	3.4 cm	
Package 1 Width	8.6 cm	
Package 1 Length	8.6 cm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile