

Product datasheet

Specifications



AvatarOn, USB charger, 2 type A, 2.1 A, Wood

E8332USB_WD_G2

Main

Product or component type	USB charger
Integrated connection type	2 USB type A 5 V DC, maximum load current: 2.1 A

Complementary

Device mounting	Flush
Device presentation	Complete product
Colour tint	Wood
Surface finish	Glossy
[Ue] rated operational voltage	100/240 V AC 50/60 Hz
Maximum load current with 2 outputs used simultaneously	2.1 A
Material	PC (polycarbonate)
Connections - terminals	Screw terminals
Screwdriver shape	Phillips combined
Clamping connection capacity	1.5...2.5 mm ² for flexible cable(s) 1.5...2.5 mm ² for rigid cable(s)
Height	86 mm
Width	86 mm
Depth	40 mm

Environment

Standards	IEC 60950-1
Electrical insulation class	Class II
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	100.0 g
Package 1 Height	3.4 cm
Package 1 Width	8.6 cm

Package 1 Length	8.6 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Weight	880.0 g
Package 2 Height	9.5 cm
Package 2 Width	19.0 cm
Package 2 Length	19.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile