

# Product datasheet

Specifications



## Trailing socket, AvatarOn, with individual switch & USB, 6 gang, 3M, white

TSH36U\_3\_WE\_C5

### Main

Range	AvatarOn
Product or component type	Power strip
Control type	Switch
Socket number	6
Integrated connection type	2 USB port 5 V DC, maximum load current: 2.4 A
Cable length	3 m
Colour tint	White

### Complementary

Number of socket outlets with earth pin	6
[Ue] rated operational voltage	250 V
Number of USB connection	2
[In] rated current	13 A
Outlet standard	BS 1363
Socket additional information	Shuttered
Pilot light	ON indicator
Material	PC (polycarbonate)
Length	400.5 mm
Width	61 mm
Depth	32 mm
Type of packing	Blister
Cable cross section	0...1.25 mm <sup>2</sup>
Height	32 mm
Net weight	0.742 kg

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	884.0 g

Package 1 Height	7.4 cm
Package 1 Width	8.0 cm
Package 1 Length	46.0 cm
Unit Type of Package 2	S04
Number of Units in Package 2	12
Package 2 Weight	11.368 kg
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Unit Type of Package 3	P12
Number of Units in Package 3	144
Package 3 Weight	148.416 kg
Package 3 Height	105.0 cm
Package 3 Width	80.0 cm
Package 3 Length	120.0 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>