



Less hassle, more savings

Essential SmartBright Slim Batten

A flexible solution for long linear light for ambient lighting.

Benefits

- Easy to install, easy to hide
- Save energy consumption
- Easy to choose, flexible

Features

- Slim profile
- Mix and match
- High Efficacy

Application

- Shop Window
- Cove
- Convenience Store

Essential SmartBright Slim Batten

Versions



BN068C LED3

BN068C LED5

BN068C LED9

BN068C LED11

Application Conditions	
Ambient temperature range	-20 to +35 °C
Average ambient temperature	25 °C
Maximum dim level	Not applicable
Approval and Application	
Mech. impact protection code	IK02
Ingress protection code	IP20
Controls and Dimming	
Dimmable	No
Operating and Electrical	
Input Voltage	220-240 V
General Information	
CE mark	-
Protection class IEC	Safety class I
Driver included	Yes
ENEC mark	-
Flammability mark	-
Light source replaceable	No
Optic type	-
UL mark	-
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Mechanical and Housing	
Color	White

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial Input power
911401504131	BN068C LED3/CW L300	6500 K	4 W
911401504231	BN068C LED3/NW L300	4000 K	4 W
911401504331	BN068C LED3/WW L300	-	4 W
911401504431	BN068C LED5/CW L600	6500 K	7 W
911401504531	BN068C LED5/NW L600	4000 K	7 W
911401504631	BN068C LED5/WW L600	-	7 W
911401504731	BN068C LED9/CW L900	6500 K	10 W
911401504831	BN068C LED9/NW L900	4000 K	10 W
911401504931	BN068C LED9/WW L900	-	10 W
911401505031	BN068C LED11/CW L1200	6500 K	14 W
911401505131	BN068C LED11/NW L1200	4000 K	14 W
911401505231	BN068C LED11/WW L1200	-	14 W

Essential SmartBright Slim Batten

