EU-TYPE EXAMINATION CERTIFICATE



[2] Equipment or Protective System intended for use in Potentially Explosive Atmospheres
Directive 2014/34/EU

- [3] EU-Type Examination Certificate Number: UL 22 ATEX 2543X Rev. 0
- [4] Product: LED Luminaries, Models CES-EX-GB-02 series, CES-EX-LN-02 series
- [5] Manufacturer: Shenzhen CESP Co., Ltd.

[1]

- [6] Address: 6th Fl Wangcheng Bldg., Longhua St., Longhua District, Shenzhen, Guangdong, 518109, China
- [7] This product and any acceptable variation thereto are specified in the schedule to this certificate and the documents therein referred to
- [8] UL International Demko A/S, notified body number 0539 in accordance with Article 17 of the Council Directive 2014/34/EU of 26 February 2014, certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to design and construction of products intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential report no. US/UL/ExTR22.0094/00.

[9] Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN IEC 60079-0:2018

EN 60079-31:2014

- [10] If the sign "X" is placed after the certificate number, it indicates that the product is subject to special conditions for safe use specified in the schedule to this certificate.
- [11] This EU-Type Examination Certificate relates only to the design and construction of the specified product. Further requirements of the Directive apply to the manufacturing process and supply of this product. These are not covered by the certificate.
- [12] The marking of the product shall include the following:



Certification Manager
Jan-Erik Storgaard

This is to certify that the sample(s) of the Product described herein ("Certified Product") has been investigated and found in compliance with the Standard(s) indicated on this Certificate, in accordance with the ATEX Product Certification Program Requirements. This certificate and test results obtained apply only to the product sample(s) submitted by the Manufacturer. UL did not select the sample(s) or determine whether the sample(s) provided were representative of other manufactured product. UL has not established Follow-Up Service or other surveillance of the product. The Manufacturer is solely and fully responsible for conformity of all product to all applicable Standards, specifications, requirements or Directives. The test results may not be used, in whole or in part, in any other document without UL's prior written approval.

Date of issue: 2022-11-29

[13] [14]

Schedule EU-TYPE EXAMINATION CERTIFICATE No.

UL 22 ATEX 2543X Rev. 0

[15] <u>Description of Product</u>

The Models CES-EX-GB-02 series and CES-EX-LN-02 series of LED luminaires are suitable for use in hazardous location classified as Zone 21. Models CES-EX-GB-02 series consists of three "tb" compartments: one LED compartment, one LED driver compartment, one Junction box compartment. Models CES-EX-LN-02-x-01-y-z-D (x=40, 50 or 60) consists of two "tb" compartments: one LED compartment, one LED driver compartment. Models CES-EX-LN-02-x-01-y-z-D (x=80, 100, 120 or 150) consists of three "tb" compartments: two LED compartments, one LED driver compartment.

Nomenclature for Luminaires:

The complete luminaire catalogue number example is as follows:

Models	CES	-EX	-GB	-02	-30	-02	-01	-01	-D
	1	2	3	4	5	6	7	8	9

- 1 Designates company identification CES SHENZHEN CESP
- 2 Designates category of luminaire EX Hazardous Locations
- 3 Designates shape of luminaire
 GB Roundness (For CES-EX-GB series)
 LN Linear (For CES-EX-LN series)
- 4 Design number: 02 For all luminaires
- 5 Designates luminaire wattage

For CES-EX-GB series: 30 – 30W; 40 – 40W; 60 – 60W; 80 – 80W For CES-EX-LN series: 40 – 40W; 50 – 50W; 60 – 60W; 80 – 80W; 100 – 100W; 120 – 120W; 150 – 150W

- 6 Designates the configuration
 - 01 Line (For CES-EX-LN series)
 - 02 Roundness (For CES-EX-GB series)
- 7 Designates CCT (Correlated Color Temperature) of LED light
 - 01 3000K
 - 02 4000 K
 - 03 6500K
 - 04 5000K
 - 05 5700K
- 8 Mounting Means
 - 01 Ceiling Mount
 - 02 Wall Mount
 - 03 Pole Mount (For CES-EX-GB series)
 - 03 Drop Mount (For CES-EX-LN series)
 - 04 Drop Mount (For CES-EX-GB series only)
- 9 May be any digits or alphabet for internal use
 - D May be any digits or alphabet for internal use

Models covered are as follows:

1. CES-EX-GB-02-x-02-y z-D: x can be 30, 40, 60 or 80; y can be 01, 02, 03, 04 or 05; z can be 01, 02, 03 or 04; D can be any digits or alphabet.

Models	Ambient Temperature range	Dust Temperature Rating	
	-40°C to +40°C	T79°C	
CES-EX-GB-02-30-02-y-z-D	-40°C to +45°C	T79°C	
	-40°C to +50°C	T79°C	

CES-EX-LN-02-x-01-y-z-D: x can be 40, 50, 60, 80, 100, 120, 150; y can be 01, 02, 03, 04 or 05; z can be 01, 02 or 03; D can be any digits or alphabet.

Models	Ambient Temperature range	Dust Temperature Rating
CES-EX-LN-02-40-01-y-z-D,	-40°C to +40°C	T83°C
CES-EX-LN-02-50-01-y-z-D,	-40°C to +45°C	T83°C
CES-EX-LN-02-60-01-y-z-D	-40°C to +50°C	T83°C
CES-EX-LN-02-80-01-y-z-D,	-40°C to +40°C	T89°C
CES-EX-LN-02-100-01-y-z-D,	-40°C to +45°C	T89°C
CES-EX-LN-02-120-01-y-z-D,		T89°C
CES-EX-LN-02-150-01-y-z-D	-40°C to +50°C	



[13] [14]

Schedule EU-TYPE EXAMINATION CERTIFICATE No.

UL 22 ATEX 2543X Rev. 0

Electrical Rating:

	Models	Voltage (Vac)	Frequency (Hz)	Wattage (W) 30/40/60/80		
	CES-EX-GB-02-x-02-y-z-D(*)	100-277	50/60			
	CES-EX-LN-02-x-01-y-z-D(@)	x-01-y-z-D(@) 100-277		40/50/60/80/100/120/150		
	(*) x can be 30, 40, 60 or 80; y can be 01, 02, 03, 04 or 05; z can be 01, 02, 03 or 04; D can be any digits or alphabet. (@) x can be 40, 50, 60, 80, 100, 120, 150; y can be 01, 02, 03, 04 or 05; z can be 01, 02 or 03; D can be any digits or alphabet.					

The optical radiation output of the product with respect to explosion protection, according to Annex II clause 1.3.1 of the Directive 2014/34/EU is covered in this certificate based on Exception 2) to the scope of EN 60079-28:2015.

Routine tests:

Routine test is not required.

[16] <u>Descriptive Documents</u>

The scheduled drawings are listed in the report no. provided under item no. [8] on page 1 of this EU-Type Examination. Certificate.

[17] Specific conditions of use:

- DO NOT OPEN WHEN ENERGIZED.
- POTENTIAL ELECTROSTATIC CHARGING HAZARD SEE INSTRUCTIONS
- DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT

[18] <u>Essential Health and Safety Requirements</u>

The Essential Health and Safety Requirements (EHSRs) covered by the standards listed at item 9.

Additional information

The models CES-EX-GB-02 series, CES-EX-LN-02 series has in addition passed the tests for Ingress Protection to IP66 in accordance with EN60529:1991+A1:2000+A2:2013.



will be used as the company identifier on the marking label.

The manufacturer shall inform the notified body concerning all modifications to the technical documentation as described in Annex III to Directive 2014/34/EU of the European Parliament and the Council of 26 February 2014.

