


DLP120-1H24V (Product No.:107201030101)

Product Features


- A channel constant voltage output
- Applicable to indoor LED lights
- Small size, high efficiency, high reliability and long life time
- -20 C ~+45 C , working temp
- Protections: Over Current , Over voltage, short circuit self-recovery protection
- The typical efficiency of the machine is up to 88%
- Compliance with CE and ROHS
- 100% Full load aging test




Technical Parameters

Model	DLP120-1H24V	
	Efficiency	88%
	Voltage	220VAC-240VAC
	Frequency Range(Hz)	50/60Hz
	Power Factor	0.95
	THD(full load)	20%
	Current	0.54-0.7A
	Input Power@ None Load	0.5W
Input	Current(mA)	5A
	Voltage (VDC)	24VDC
	Power(W)	120W
	Channel	1
	Voltage Tolerance	±5%
	Voltage ripple	300 mV
	Turn-on delay time	0.8s
	Thermal protection	110 degree
Output	Short Circuit	Yes
	Over Voltage	Yes
	Over Current	Yes
Protection	Surge	L-N:1.2kV test
	Withstand Voltage	Input-output: >3.75kV
	Performance standard	IEC 62384:2006, GB24825-2009
	Immunity & EMI	EN55015、 EN61547
Safety& EMC	Working Temp.	-20°C-45°C
	Storage Temp., Humidity	-20°C-80°C, 5-95%RH
	tc	90°C
	Material	PC
Others	IP Rating	IP20
	Life by T case Life	50,000h@80 C
	Warranty Condition	5 years
	Switch Cycle	>25,000 times
	Packing(weight)	Net weight: 455g±5%/PCS; 25PCS/Carton; 11.4kg±5%/Carton; Carton Size:32*24*20mm(L*W*H)
	Dimension	300*40*30mm (L*W*H)


Dimension(mm)




Wiring




Power factor versus output power




Efficiency versus output power



THD versus output power



Driver lifetime versus Tc temperature



Cautions

- 1.The product shall be installed and serviced by a qualified person.
- 2.This product is non-waterproof. Please avoid the sun and rain. When installed outdoors please ensure it is mounted in a water proof enclosure.
- 3.Good heat dissipation will prolong the working life of the controller. Please ensure good ventilation.
- 4.Please check if the output voltage and current of any LED power supplies used comply with the requirement of the product.
- 5.Please ensure that adequate sized cable is used from the controller to the LED lights to carry the current. Please also ensure that the cable is secured tightly in the connector.
- 6.For safety consideration, PVC or rubber cord of 0.75-1.5mm² is recommended for input and output terminal(s) .Flat power cord is not suitable. Ensure all wire connections and polarities are correct before applying power to avoid any damages to the LED lights.
- 7.The power supply should be strictly and reliably grounded to prevent electric shock.
- 8.If a fault occurs please return the product to your supplier. Do not attempt to fix this product by yourself.

※ The contents of this manual are updated without prior notice. If the function of the product you are using is inconsistent with the instructions, the function of the product shall prevail.Please contact us if you have any questions .

DLP120-1H24V (产品代码:107201030101)

产品特点

- 单通道恒压输出
- 适用于LED室内灯具
- 小体积、高效率、高可靠、长寿命
- 在-20°C~+45°C工作正常
- 保护种类：过流、过压、短路自恢复保护
- 整机典型效率高达88%
- 符合CE认证，符合RoHS环保标准
- 100%满载老化测试



应用



洗墙灯



LED灯带



LED硬灯条



地埋灯




AR斗胆灯




技术参数

型号	DLP120-1H24V	
输入	效率	88%
	电压	220VAC-240VAC
	频率	50/60Hz
	功率因素	0.95
	THD	20%
	电流	0.54-0.7A
	空载输入功率	0.5W
输出	电流	5A
	电压	24VDC
	功率	120W
	通道	1
	电压公差	±5%
	电压纹波	300 mV
	待机功耗	0.5W
	启动延时	0.8s
保护	热保护	110度
	短路	有
	过流	有
安全 & 电磁兼容	过压	有
	浪涌	L-N:1.2kV test
	耐压标准	Input-output: >3.75kV
	性能标准	IEC 62384:2006, GB24825-2009
其它	电磁兼容	EN55015、EN61547
	工作温度	-20°C~45°C
	储存温度、湿度	-20°C~80°C, 5-95%RH
	tc	90°C
	材质	PC
	防水等级	IP20
	寿命	50,000h@80 C
	质保	5年
	开关周期	>25,000次
	包装尺寸(重量)	净重: 455g±5%/PCS; 25PCS/Carton; 11.4kg±5%/箱; 外箱尺寸: 32*24*20cm(长*宽*高)
	尺寸	300*40*30mm (长*宽*高)


尺寸(mm)




接线图:




功率因数与输出功率




效率与输出功率



THD 与输出功率



驱动寿命温度



注意事项:

- 1、本产品请由具有专业资格的人员进行调试安装。
- 2、本产品不能防水，需避免日晒雨淋，如安装在户外，请用防水箱。
- 3、良好的散热条件会延长产品的使用寿命，请把产品安装在通风良好的环境。
- 4、请检查使用的LED电源输出电压电流，是否符合产品要求。
- 5、使用的电线直径大小必须能够负载连接的LED灯具，并确保接线牢固，以免电线过热或接触不良触发事故。
- 6、通电调试前，应确保所有接线正确，以避免因接线错误而导致灯具损坏。
- 7、安装在金属表面，电源应严格可靠接地，以防漏电触电。
- 8、如果发生故障，请勿私自维修；如有疑问，请联系供应商。

※ 本说明书内容如有更新，恕不另行通知。

若您使用的产品功能与说明书不一致时，请以产品为准。如有疑问请与我们联系。