

CONTROL SYSTEM

控制系统
DMX-SA 系列



DMX-SA-21

Features 产品特点

- * 支持标准USITT DMX512/1990协议
- * 支持DMX信号双向传输
- * 高性能DMX通信芯片，强大的信号放大性能，每个端口支持128个节点
- * 双电源设计，完善的保护机制，输入输出DMX信号带光电隔离保护
- * Supports standard USITT DMX512/1990 protocol.
- * DMX signal support bidirectional transmission.
- * High-performance DMX communication chip, a powerful signal amplification performance, each port supports 128 nodes
- * Dual power supply design, perfect protection mechanism, DMX input and output signals with optical isolation protection.

标配型号 & 技术参数 \ Model Info & Specifications

型号/Model	DMX-SA-21
尺寸/Size	L200xW89xH61mm
材质/Main body	ABS
重量/Weight	1.5kgs±5%
输入电压/Input Volt	120-240V AC
最大功率/Power Max.	2W
端口/Terminal	3 Pin IP68 Connector
兼容性/Compatible	ALL DMX Fixtures

CONTROL SYSTEM

控制系统
系列 DMX-SA



DMX-EAS-24V

Features 产品特点

- * 简易控制器方便样品使用
- * 低压DMX512和4线3回路2种控制方式可选
- * For sample LED fixture use simply
- * DMX or 4wires 3loops control ways for option

标配型号 & 技术参数 \ Model Info & Specifications

型号/Model	DMX-EAS-24V	CTR-EAS-24V
尺寸/Size	L200xW89xH61mm	L200xW89xH61mm
材质/Main body	ABS	ABS
重量/Weight	1.5kgs±5%	1.5kgs±5%
输入电压/Input Volt	120 or 240V AC	120 or 240V AC
最大功率/Power Max.	35W/60W	35W/60W
端口/Terminal	5 Pin IP68 Connector	4pins Naked power wire
兼容性/Compatible	所有低压DMX灯具/ALL DMX Fixtures with lower voltage	所有低压4线3回路灯具/ALL 4 wires 3 loops Fixtures with lower voltage