



General

Product Type	Constant Voltage Driver
Length (mm)	292
Width (mm)	43
Height (mm)	30
Housing Color	White
Housing Material	Plastic
Mounting	Surface mounted
Weight (g)	300

Electronics

Input Domain	AC
Input Voltage	220 ~ 240V AC
Input Current max (A)	0.5A @ 230V AC
Output Voltage	24V DC
Output Current Max. (A)	4.17
Output Power Range (W)	0~100
Power Factor at Full Load	+0.98 @ 230VAC
Anti Surge	L-N: 2kV
Leakage current max. (mA)	0.5
Standby Power Loss Max. (W)	0.5
THD (at full load)	max. 14% at 230V AC at full load
Input Frequency	50 ~ 60Hz
Inrush Current	45A @ 230VAC

Lighting

Color Range	Tunable White
-------------	---------------

Control

Output Signal	DALI DT8, PWM-CV
Control	DALI
Dimming Range	0~100%
Number of Channels	2

Protection

Protection Class	II
------------------	----

Environmental

Storage Temperature	-40 ~ +80 °C
Operating Temperature	-20 ~ +50 °C
Ingress Protection	IP20



IP20

Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. InventDesign is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make changes to our products and to change information, at its sole discretion, without notice.