EASI LED RECESSED EMERGENCY LIGHT

EmLED-12NM

















EmLED-12NM

EmLED-12NM with ring adapter

Technical Data

Mode of Operation

Lamp

Operating Temperature

Mains Supply

Power Consumption

Battery Charger

Charging Monitor

Recharge Period

Testing Facility

Emergency Duration

Safety Feature

Construction

Weight (Nett/Gross)

Compliance

.

Installation

IP Rating

Warranty

Non-maintained

Samsung 2W High flux white LED

ta 0°C ~ 50°C

230V AC 50Hz/60Hz

< 2W

High temperature NICD battery

Fully automatic

Green LED

24 hours

Test-switch for independent testing

3 hours

Low-voltage cut-off to prevent over-

discharge of battery

Polycarbonate

0.20 kg / 0.28 kg

SS 563-2:2010/A1:2013 SS IEC 60598-2-22:2016 SS IEC 60598-1:2016

Recessed mount


IP 20

1 year

Features and Application

- New compact all-in-one, self-contained LED emergency light for recessed installation on ceilings designed for easy installation and usage.
- Includes a ring adapter.
- Suitable for various indoor environments such as retail, commercial, hospitality and healthcare industries.
- LED lamps provide high efficiency, durability and low energy consumption.

Dimensions (mm)



Opening size: Ø 65

Ordering Information

MODEL	LAMP
EmLED-12NM	Samsung 2W High flux white LED