




S.N.	Pictures	Model	Discription	Power	LED	Input	Explosion Mark	IP Grade	Lamp Efficiency	Product Size (mm)	Net weight (kg)	Carton Dimension(mm), 1 pc/ CTN	G.W.(kg)/CTN, 1 pc per carton
1		EPTL08	SS base, cover made of high quality PC which is light weight, high strength, impact resistant, hot resistant, corrosion resistant,waterproof, dust proof, corrosion-resistant.	20W	SMD	105-277VAC/50, 60Hz or DC	Ex e mb II C T5 Gb / Ex tD A21 IP66 T95℃	IP66	100lm/W	680x142x90	2.50	745x198x132	3.00
2		EPTL08	SS base, cover made of high quality PC which is light weight, high strength, impact resistant, hot resistant, corrosion resistant,waterproof, dust proof, corrosion-resistant.	40W	SMD	105-277VAC/50, 60Hz or DC	Ex e mb II C T5 Gb / Ex tD A21 IP66 T95℃	IP66	100lm/W	680x142x90	2.50	745x198x132	3.00
3		EPTL08	SS base, cover made of high quality PC which is light weight, high strength, impact resistant, hot resistant, corrosion resistant,waterproof, dust proof, corrosion-resistant.	50W	SMD	105-277VAC/50, 60Hz or DC	Ex e mb II C T5 Gb / Ex tD A21 IP66 T95℃	IP66	100lm/W	1285x142x90	4.50	1320x198x132	5.10