



Overview

Mounting	Recessed ceiling
Material	Aluminum, paint; Plastic mounting ring
Cut-out	150mm
Finishing	White
IP rating	54

Electrical

Power supply	220-240Vac
Gear	LED Driver
Dimming	Triac/ 1-10V/ DALI
Installation	Remote
Insulation class	III
Output voltage	32.4-39.6V
Current intensity	350mA
Driver lifespan	40,000Hrs
Certification	CE/ IP Report

Accessories

N/A

Lamp

Light source	LED																		
Power	13W																		
Nominal flux	1972.28Lm																		
Optical efficiency	80.3%																		
Fixture flux	1583.74Lm																		
Color temperature	4000K																		
SDCM	3																		
CRI	80																		
Beam angle	75°																		
Tilting angle	-																		
Rotating angle	-																		
LED lifespan	50,000Hrs L80B10																		
Photometric	<table border="1"> <thead> <tr> <th colspan="3">Beam angle 75° 4000K</th> </tr> </thead> <tbody> <tr> <td>1036</td> <td>1.535</td> <td>1.0</td> </tr> <tr> <td>259</td> <td>3.07</td> <td>2.0</td> </tr> <tr> <td>115</td> <td>4.605</td> <td>3.0</td> </tr> <tr> <td>65</td> <td>6.14</td> <td>4.0</td> </tr> <tr> <td>E (lx)</td> <td>D (m)</td> <td>H (m)</td> </tr> </tbody> </table>	Beam angle 75° 4000K			1036	1.535	1.0	259	3.07	2.0	115	4.605	3.0	65	6.14	4.0	E (lx)	D (m)	H (m)
Beam angle 75° 4000K																			
1036	1.535	1.0																	
259	3.07	2.0																	
115	4.605	3.0																	
65	6.14	4.0																	
E (lx)	D (m)	H (m)																	

Beam angle 75° 4000K		
1036	1.535	1.0
259	3.07	2.0
115	4.605	3.0
65	6.14	4.0
E (lx)	D (m)	H (m)



Dimension

