

LED DOWNLIGHT

Slim Recessed/Surface Mount LED Downlight

**Dimmable
NEW!**



EcoMax-III Round or Square Recessed Downlight with remote LED Driver (Dimmable / Non-dimmable)



EcoMax-II Round or Square Recessed Downlight with integrated LED Driver (Non-dimmable)

EcoMax-III (Dimmable / Non-dimmable) CRI >80

No.	Item code	Power (W)	Power Factor	Lumen (lm)	Input Current (mA)	Dimension (mm)	Cut-out (mm)	CCT (K)
P3-1	LED-DownlightRc-ESIII-R100-6W (dim/non-dim)	6	0.5	450-480	60	Ø112 x H29	Ø100	3000/4000/6500
P3-2	LED-DownlightRc-ESIII-R150-12W (dim/non-dim)	12	0.5	900-960	105	Ø162 x H29	Ø150	3000/4000/6500
P3-3	LED-DownlightRc-ESIII-R200-18W (dim/non-dim)	18	0.5	1350-1440	150	Ø212 x H29	Ø200	3000/4000/6500
P3-4	LED-DownlightRc-ESIII-R200-24W (dim/non-dim)	24	0.5	1800-1920	180	Ø212 x H29	Ø200	3000/4000/6500
P3-5	LED-DownlightRc-ESIII-S100-6W (dim/non-dim)	6	0.5	450-480	60	112x112xH29	100x100	3000/4000/6500
P3-6	LED-DownlightRc-ESIII-S150-12W (dim/non-dim)	12	0.5	900-960	105	162x162xH29	150x150	3000/4000/6500
P3-7	LED-DownlightRc-ESIII-S200-18W (dim/non-dim)	18	0.5	1350-1440	150	212x212xH29	200x200	3000/4000/6500
P3-8	LED-DownlightRc-ESIII-S200-24W (dim/non-dim)	24	0.5	1880-1920	180	212x212xH29	200x200	3000/4000/6500

EcoMax-II (Non-dimmable)

No.	Item code	Power (W)	Power Factor	Lumen (lm)	Input Current (mA)	Dimension (mm)	Cut-out (mm)	CCT (K)
P3-9	LED-DownlightRc-ESII-R100-6W	6	0.45	380-400	55	Ø113 x H31	Ø100	3000/4000/6000
P3-10	LED-DownlightRc-ESII-R150-12W	12	0.5	810-850	100	Ø163 x H31	Ø150	3000/4000/6000
P3-11	LED-DownlightRc-ESII-R200-18W	18	0.5	1250-1300	155	Ø213 x H31	Ø200	3000/4000/6000
P3-12	LED-DownlightRc-ESII-R200-24W	24	0.5	1620-1700	190	Ø213 x H31	Ø200	3000/4000/6000
P3-13	LED-DownlightRc-ESII-S100-6W	6	0.45	380-400	55	113x113xH31	100x100	3000/4000/6000
P3-14	LED-DownlightRc-ESII-S150-12W	12	0.5	810-850	100	163x163xH31	150x150	3000/4000/6000
P3-15	LED-DownlightRc-ESII-S200-18W	18	0.5	1250-1300	155	213x213xH31	200x200	3000/4000/6000
P3-16	LED-DownlightRc-ESII-S200-24W	24	0.5	1620-1700	190	213x213xH31	200x200	3000/4000/6000

Accessory: Surface Mount Casing for ESII and ESIII

No.	Item code	Dimension (mm)
P3-17	LED-Downlight-SM-ESII-R100-WH	Ø115 X H60
P3-18	LED-Downlight-SM-ESII-R150-WH	Ø165 X H60
P3-19	LED-Downlight-SM-ESII-R200-WH	Ø215 X H60
P3-20	LED-Downlight-SM-ESII-S100-WH	115 X 115 X H60
P3-21	LED-Downlight-SM-ESII-S150-WH	165 X 115 X H60
P3-22	LED-Downlight-SM-ESII-S200-WH	215 X 215 X H60



Round Surface Mount Casing



Square Surface Mount Casing



Surface Mount Version

LED Ecomax Spot

NEW!



LED-SpotRA-HS-7W (Adjustable)



LED-SpotRA-HQ-7W/9.5W Dimmable (Adjustable)



LED-SpotRA-E-4.5W (Adjustable)



LED-SpotRF-EII-4W (Fixed)



LED-SpotRF-E-2W (Fixed)

No.	Item code	Power (W)	Power Factor	Lumen (lm)	Input Current (mA)	Beam Angle (°)	UGR	Dimension (mm)	Cut-out (mm)	CCT (K)
P3-23	LED-SpotRA-HS-R70-7W-WH	7	0.5	400	52	-	-	Ø86 x H37	Ø70	3000/4000/5700
P3-24	LED-SpotRA-HQ-7W-Dim	7	0.90	420	36	24/40	13	Ø91 x H60	Ø80	3000/4000/5700
P3-25	LED-SpotRA-HQ-9.5W-Dim	9.5	0.90	600	45	24/40	13	Ø91 x H57	Ø80	3000/4000/5700
P3-26	LED-SpotRA-E-4.5W-30D-WH	4.5	0.52	250	37	30	13	Ø68 x H58	Ø60	3000/4000/5700
P3-27	LED-SpotRF-EII-4W-WH	4	0.55	170	31.8	-	16	Ø72 x H63	Ø63	3000/5700
P3-28	LED-SpotRF-E-2W-25D-WH	2	0.40	80	22	-	-	Ø35 x H15.5	Ø30	3000/4000/6500