

GL-HO-G2 120-865 L60X60

GinoLED HO Module G2 | LED modules for street lighting

Areas of application

- Airports, stations and factories
- Indoor courts, exhibition halls, warehouses



Product family benefits

- High module efficacy: up to 165 lm/W
- Integrated heat sink for optimal thermal management and tailored optical design
- Light weight design for easy installation



Product datasheet

Product family features

- Available with beam angle: 60°×60° and 90°×90°
- Available with color temperature: 4,000 K, 6,500 K
- Color rendering index R_a : 80
- Impact resistance: IK08
- Type of protection: IP65
- Lifetime (L70/B50): 50,000 h
- Operating temperature range: -30...45 °C
- Certificates: CE, CB, CQC
- Lifetime (L70/B50) for GL-HO 80: 50,000 h (temperature at $T_p = 50$ °C)
- Lifetime (L70/B50) for GL-HO 120: 50,000 h (temperature at $T_p = 55$ °C)
- Lifetime (L70/B50) for GL-HO 150/180: 50,000 h (temperature at $T_p = 60$ °C)

Product datasheet

Technical data


Electrical data

| | |
|-----------------|-------|
| Nominal current | 0.7 A |
| Type of current | DC |

Photometrical data

| | |
|--------------------------|----------|
| Luminous efficacy | 165 lm/W |
| Color temperature | 6500 K |
| Color rendering index Ra | >80 |

Dimensions & weight



| | |
|----------------|-----------|
| Product weight | 2100.00 g |
| Length | 296.0 mm |

Temperatures & operating conditions

| | |
|--|-------------|
| Temperature range in operation at T _c point | -30...45 °C |
| Temperature range at storage | -40...80 °C |

Lifespan

| | |
|----------|-----------------------|
| Lifespan | 50000 h ¹⁾ |
|----------|-----------------------|

¹⁾ L70/B50 at T_p normal

Capabilities

| | |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

Certificates & standards

| | |
|--------------------|------|
| Type of protection | IP65 |
|--------------------|------|

Product datasheet

| | |
|------------------|--|
| Standards | Acc. to IEC 62778/Acc. to IEC 60598-1/Acc. to EN 62031/Acc. to EN 55015/Acc. to EN 61547/Acc. to IEC 61000-3-2/Acc. to IEC 61000-3-3 |
|------------------|--|

Logistical data

| | |
|-----------------------|--------------|
| Commodity code | 940540999000 |
|-----------------------|--------------|

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-------------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4062172051477 | GL-HO-G2 120-865 L60X60 | Shipping carton box 1 | 362 mm x 362 mm x 189 mm | 24.77 dm ³ | 2896.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.