

# LUMINAIRE SPECIFICATION

**PROJECT :**



\*Above picture for illustration purposes only.



Technical Parameters	
Ex Marking	Ex d e IIC T6 Gb / DIP A20 TA, T6
IP Degree	IP66
Corrosion Resistant	WF1
Rated Voltage	220VAC/50-60HZ
Conduit Entries	M20
Battery Back-up	Optional, Emergency time>90min; Charging time: 24h; Starting time: 0,3s
Mounting Styles	Pendant; Ceiling; Chain; Embedded; Wall; Stanchion

Type :	LED Ex-proof linear light	Location :	
Model :	BYS-K LED SERIES	Legend :	Quantity:
Lamp Source:	LED tube	Control Gear :	Built-in LED tube
Color Temp :	6500K	Lumen:	2X1050lm
Description :	LUMENEX BYS-K SERIES, 2x8W LED explosion-proof linear light fitting suitable for zone 1,21 2& 22, c/w 2x8W LED tube, daylight total 2100lm, GRP housing & PC diffuser, IP66, ATEX certified.	IP Rating :	IP66
		Dimension:	As shown above
		Country of Origin :	PRC
		Comments:	
Submitted Date:	Revision:	Approved by:	Signature:
		Architect	
		Consultant	