
ROCKY









Dimension: mm NTS

TECHNICAL DATA

Mode of Operation : Non-Maintained

Lamp : Maxspid 3W SMT LED Lamp

Rated Duration : 3 hrs and others

Mains Supply : 230 Volts, 50/60Hz

Power Consumption: < 2W

Battery : High temp Nickel Cadmium

Charge Monitor : Green LED
Test Facility : Tactile switch

Safety Feature : Low volt cut-off preventing battery overdischarge

Housing : Injection moulded fire retardant high impact polycarbonate

diffuser and base. Clear reeded diffuser is designed for

non-glare and greater light distribution

Mounting : Wall or ceiling
Cable Entry : Ø20mm K/O hole
Weight : 0.6 kg (gross)

Compliance : SS 563 : Part 1 & 2, SS IEC 60598-2-22

Warranty : 1 year

KEY FEATURES

- > Using Surface Mount Technology LED
- > High Durability & Reliability
- > Low Heat
- > Low Maintenance
- > Low Power Consumption
- > No "Black Ends"

Type and batch tested with PSB PLS-LISTED LABEL



Surface Mount Compact Emergency Luminaire





ORDERING GUIDE (Please check with Sales Dept if customisation is required)

Model	Lamp	Battery type
MEW.3.NC180.NM	3W SMT LED	Nickel Cadmium

Note:

Optional silkscreen printed legend on cover to convert into an emergency exit light.

*Heating strip applicable (for cold room used)



