




### LED Recessed Downlight





HR- A downlight with impressive appearance especially for office application



HM-A downlight with high efficiency which can perfectly fit in the energy saving programs and commercial application.



Visual Comfort - The wall and objects in glare free area can be easily caught and highlight



Item Code	Power (W)	Dimension (mm)	CRI	Lumen (lm)	CCT(K)
OPL MTD07002A12 07 HR 5W	5	Ø90 x H46.7	80	330	3000
OPL MTD0700312 07 HR 6W	6	Ø110 x H61.7	80	430	3000
OPL MTD0700412 07 HR 9W	9	Ø130 x H69.5	80	700-750	3000/4000
OPL MTD0700612 07 HR 14W	14	Ø185 x H90.3	80	1220-1320	3000/4000
OPL MTD0700812 08 HR 29W	29	Ø220 x H113.3	80	2300-2500	3000/4000
OPL MTD0700812 09 HR 42W	42	Ø220 x H113.3	80	3400-3650	3000/4000
OPL MTD0700412 HM 9W	9	Ø130 x H69.5	80	700	3000
OPL MTD0700612 HM 14W	14	Ø185 x H90.3	80	1100	3000

### LED Slim Recessed Downlight



OPL-RC-ESII S150/S200



OPL-RC-ESII R150/R200



OPL-RC-ES S100/S150/S175



OPL-RC-ES R100/R150/R175




SR CP Series



SS CP Series

Item Code	Power (W)	Dimension (mm)	CRI	Lumen (lm)	CCT(K)
OPL-RC-ESII-R150-12W	12	Ø163 x H31	80	810-850	3000/4000/6000
OPL-RC-ESII-S150-12W	12	163 x 163 x H31	80	810-850	3000/4000/6000
OPL-RC-ESII-R200-18W	18	Ø213 x H31	80	1250-1300	3000/4000/6000
OPL-RC-ESII-R200-24W	24	Ø213 x H31	80	1620-1700	3000/4000/6000
OPL-RC-ESII-S200-24W	24	213 x 213 x H31	80	1620-1700	3000/4000/6000
OPL-RC-ES-R100-6W	6	Ø113 x H26	80	360-380	3000/4000/6000
OPL-RC-ES-R150-12W	12	Ø163 x H26	80	800-880	3000/4000/6000
OPL-RC-ES-R175-18W	18	Ø188 x H26	80	1200-1320	3000/4000/6000
OPL-RC-ES-S100-6W	6	113 x 113 x H26	80	380-400	3000/4000
OPL-RC-ES-S150-12W	12	165 x 165 x H26	80	820-870	3000/4000
OPL-RC-ES-S175-18W	18	190 x 190 x H26	80	1230-1320	3000/4000
OPL MTD006 SR CP	6	Ø120 x H13	70	340-350	3100/4100
OPL MTD012 SR CP	12	Ø170 x H13	70	780-800	3100/4100
OPL MTD018 SR CP	18	Ø195 x H13	70	1050-1100	3100/4100
OPL MTD006 SS CP	6	120 x 120 x H13	70	340-350	3100/4100
OPL MTD012 SS CP	12	170 x 170 x H13	70	780-800	3100/4100
OPL MTD018 SS CP	18	195 x 195 x H13	70	1050-1100	3100/4100

Light distribution curve:



(6W/12W/18W)

Accessory for OPL-RC-ESII series-trimless version:



### LED EcoMax Spot



SPOTRA HQ (dimmmable)



SPOTRA E4 (non-dimmable)




SPOTRF E11 (non-dimmable)



OPL LEDSPOTRF-E-2W (non-dimmable)

Item Code	Power (W)	Dimension (mm)	CRI	Lumens (lm)	CCT(K)
OPL SPOTRA HQ 7 Dim - 24Deg	7	Ø91 x H60	80	420	3000/4000
OPL SPOTRA HQ 7 Dim - 40Deg	7	Ø91 x H60	80	420	3000/4000
OPL SPOTRA HQ 9.5 Dim - 24Deg	9.5	Ø91 x H60	80	600	3000/4000
OPL SPOTRA HQ 9.5 Dim - 40Deg	9.5	Ø91 x H60	80	600	3000/4000
OPL SPOTRA E4 5W Non-Dim	5	Ø68 x H58	80	250	3000/4000/5700
OPL SPOT RF E11 4W 3K Non-Dim	4	Ø72 x H63	80	170	3000
OPL SPOT RF E11 4W 57K Non-Dim	4	Ø72 x H63	80	190	5700
OPL LEDSPOTRF-E-2W-25D AL Non-Dim	2	Ø35 x H15.5	80	80	3000/4000/6500

Light distribution curve:



SpotRA HQ-24°(5W/7.5W)