

E8231BPL1_WE

10A 250V 1 Gang Bell Press Switch with Fluorescent Locator, White



Main

Range	Pieno
Product or component type	Switch
Switch application	Bell
Load type	Resistive
Cover frame colour tint	White

Complementary

Device mounting	Flush Surface
Wiring device mounting	Flush Surface
Switch function	Momentary
Rated current	10 A at 250 V AC 50 Hz
Local signalling	Fluorescent (white)
Number of gangs	1 gang
Material	Polycarbonate: surround Polycarbonate: grid plate
Connections - terminals	Pillar terminals
Clamping connection capacity	2 x 1.5 mm ² for stranded cable(s) 2 x 2.5 mm ² for solid cable(s)
Embedding depth	23 mm
Width	87 mm
Height	87 mm
Depth	23 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %

Standards	MS IEC 60669-1 BS EN 60669-1 GB 16915.1 IEC 60669-1 SS 227-1
-----------	--

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------