



Main

| | |
|---------------------------|--------------------------|
| Range | Pieno |
| Product or component type | Switch |
| Switch application | Switch |
| Load type | Resistive Fluorescent |
| Cover frame colour tint | White |

Complementary

| | |
|------------------------------|---|
| Device mounting | Flush Surface |
| Wiring device mounting | Flush Surface |
| Switch function | 1-way |
| Rated current | 16 AX at 250 V AC 50 Hz |
| Local signalling | Neon |
| Number of gangs | 1 gang |
| Material | Polycarbonate: surround Polycarbonate: grid plate |
| Connections - terminals | Pillar terminals |
| Clamping connection capacity | 3 x 2.5 mm ² for solid cable(s) 4 x 1.5 mm ² for stranded cable(s) |
| Embedding depth | 23 mm |
| Width | 87 mm |
| Height | 87 mm |
| Depth | 35.5 mm |

Environment

| | |
|---------------------------------------|--|
| Ambient air temperature for operation | -5...40 °C |
| Relative humidity | 0...95 % |
| Standards | GB 16915.1 MS IEC 60669-1 SS 227-1 IEC 60669-1 BS EN 60669-1 |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|
