



Main

| | |
|---------------------------|--------------------------|
| Range of product | Pieno |
| Product or component type | Switch |
| Switch function | 2-way |
| Switch application | Switch |
| Rated current | 16 AX at 250 V AC 50 Hz |
| Local signalling | Fluorescent (white) |
| Number of gangs | 3 gangs |
| Load type | Resistive Fluorescent |

Complementary

| | |
|------------------------------|---------------------------------------------------------------------------------------------|
| Wiring device mounting | Surface Flush |
| Material | Polycarbonate: surround Polycarbonate: grid plate |
| Connections - terminals | Pillar terminals |
| Clamping connection capacity | 2 x 1.5 mm ² for stranded cable(s) 2 x 2.5 mm ² for solid cable(s) |
| Width | 87 mm |
| Height | 87 mm |

Environment

| | |
|---------------------------------------|---------------------------|
| Ambient air temperature for operation | -5...40 °C |
| Relative humidity | 0...95 % |
| Standards | IEC 60669-1 GB 16915.1 |
| Product certifications | CCC |

Offer Sustainability

| | |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |