# Product datasheet Characteristics

## E82T25USB\_LS\_G2

13A Twin Gang Switched Socket with 2.1A USB, Lavender Silver





#### Main

Range	Pieno	
Product or component type	Power socket-outlet + USB charger	
Device presentation	Mechanism	
Socket additional information	Shuttered	
Colour tint	Lavender silver	
Load type	No inductive load	

#### Complementary

	(
1	
Flush 47 mm	
ON/OFF power-socket outlet	- (
2 x 2P + E with shutters, British	7
Power circuit: 13 A 220250 V, AC, 50/60 Hz	-
Glossy	
Painted	<u>.</u>
2 gangs	, c
USB type A	
220250 V AC 50/60 Hz	
0.075 W	
16 W	7
2 USB port 5 V DC, maximum load current: 2.1 A	
Polycarbonate: grid plate Polycarbonate: cover Polycarbonate: surround Polycarbonate: dolly Nylon + GF: shutter Brass: contact plate Steel: spring Nickel steel: terminal screw	Tale of State of Stat
	ON/OFF power-socket outlet  2 x 2P + E with shutters, British  Power circuit: 13 A 220250 V, AC, 50/60 Hz  Glossy  Painted  2 gangs  USB type A  220250 V AC 50/60 Hz  0.075 W  16 W  2 USB port 5 V DC, maximum load current: 2.1 A  Polycarbonate: grid plate Polycarbonate: cover Polycarbonate: surround Polycarbonate: dolly Nylon + GF: shutter Brass: contact plate Steel: spring

Protection type	USB port: over temperature protection with PWM IC circuit USB port: over voltage protection against surges with PWM IC circuit USB port: overcurrent between output phases and earth (on power up only) with PWM IC circuit
Shape of screw head	Cross
Screwdriver shape	Philips
Electrical connection	3 screw terminal
Clamping connection capacity	1 x 4 mm² for solid cable(s) 2 x 4 mm² for stranded cable(s) 1 x 2.5 mm² 2 x 2.5 mm²
Wire stripping length	1012 mm
Mounting support	Mounting box conforming to BS 4662
Fixing mode	By screws M3.5 x 25 mm
Fixing center	120.6 mm
Product compatibility	Smartphone Apple HW HTC Tablet PC Samsung Power bank XiaoMi
Height	147 mm
Width	87 mm
Depth	38.6 mm
Embedding depth	29.5 mm
Net weight	0.166 kg

#### Environment

Operating altitude	<= 2000 m
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-560 °C
Relative humidity	095 %
Standards	BS 1363-2 IEC 60950-1
Product certifications	IEC
IP degree of protection	IP20
Environmental characteristic	Alcohol Liquid soap

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	