Product datasheet Characteristics

E82T25USB_WG_G2

13A Twin Gang Switched Socket with 2.1A USB, Wine Gold





Main

Range	Pieno	,
Product or component type	Power socket-outlet + USB charger	
Device presentation	Mechanism	
Socket additional information	Shuttered	
Colour tint	Wine gold	
Load type	No inductive load	

Complementary

	(
1	
Flush 47 mm	
ON/OFF power-socket outlet	- (
2 x 2P + E with shutters, British	7
Power circuit: 13 A 220250 V, AC, 50/60 Hz	-
Glossy	
Painted	<u>.</u>
2 gangs	, , , , , , , , , , , , , , , , , , ,
USB type A	
220250 V AC 50/60 Hz	
0.075 W	
16 W	7
2 USB port 5 V DC, maximum load current: 2.1 A	
Polycarbonate: grid plate Polycarbonate: cover Polycarbonate: surround Polycarbonate: dolly Nylon + GF: shutter Brass: contact plate Steel: spring Nickel steel: terminal screw	Tale of State of Stat
	ON/OFF power-socket outlet 2 x 2P + E with shutters, British Power circuit: 13 A 220250 V, AC, 50/60 Hz Glossy Painted 2 gangs USB type A 220250 V AC 50/60 Hz 0.075 W 16 W 2 USB port 5 V DC, maximum load current: 2.1 A Polycarbonate: grid plate Polycarbonate: cover Polycarbonate: surround Polycarbonate: dolly Nylon + GF: shutter Brass: contact plate Steel: spring

Protection type	USB port: over temperature protection with PWM IC circuit USB port: over voltage protection against surges with PWM IC circuit USB port: overcurrent between output phases and earth (on power up only) with PWM IC circuit
Shape of screw head	Cross
Screwdriver shape	Philips
Electrical connection	3 screw terminal
Clamping connection capacity	1 x 4 mm² for solid cable(s) 2 x 4 mm² for stranded cable(s) 1 x 2.5 mm² 2 x 2.5 mm²
Wire stripping length	1012 mm
Mounting support	Mounting box conforming to BS 4662
Fixing mode	By screws M3.5 x 25 mm
Fixing center	120.6 mm
Product compatibility	HTC Apple Samsung XiaoMi Power bank Tablet PC Smartphone HW
Height	147 mm
Width	87 mm
Depth	38.6 mm
Embedding depth	29.5 mm
Net weight	0.166 kg

Environment

<= 2000 m
040 °C
-560 °C
095 %
IEC 60950-1 BS 1363-2
IEC
IP20
Liquid soap Alcohol

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	