

## Start Highbay

START Highbay IP65 1-10V 26000lm 840 MB

0039346



### Product features

- START Highbay, includes 1 m cables, black aluminium housing, 26,000 Lm, 200 W, 130 Lm/W, 4000 K, drive current: 5000 mA, CRI 80, 60° beam angle, 1-10 V dimmable, IP65, IK08, 50,000 hrs (L80/B50), (D x H) 339 x 194 mm.



## PRODUCT OVERVIEW

IPC Code	0039346
Product name	START Highbay IP65 1-10V 26000lm 840 MB
Technology	LED
Housing	Aluminium alloy
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Certifications	EUNEW009
ETIM Class	EC001716
E-number FI	4306964
Fixture luminous flux (lm)	26000
Luminaire efficacy (lm/W)	130
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	60
Glare control	25.1
Photobiological Risk Group	RG1
Total power consumption (W)	200
Electrical protection	Class I
Control gear type	Dimmable 1-10V analogue
Dimmable	Yes
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Average life (Nominal) (h)	50000
Housing colour	Black
IP rating	IP65
IK rating	IK08
Product EAN number	5410288393469
Lamps	Yes
Included lamp	INTEGRATED LED

## Start Highbay

START Highbay IP65 1-10V 26000lm 840 MB

0039346

### DATA TABLE

#### General data

IPC Code	0039346
Product name	START Highbay IP65 1-10V 26000lm 840 MB
Technology	LED
Housing	Aluminium alloy
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Operating Temperature Range (°C)	-30 to +50
Certifications	EUNEW009
ETIM Class	EC001716
E-number FI	4306964

#### Optical data

Fixture luminous flux (lm)	26000
Luminaire efficacy (lm/W)	130
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	60
Distribution type	Direct
Glare control	25.1
Photobiological Risk Group	RG1

#### Electrical data

Total power consumption (W)	200
Mains voltage (V)	220-240V~
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	10
Electrical protection	Class I
Control gear type	Dimmable 1-10V analogue
Dimmable	Yes
Minimum dimming level (%)	1
Drive current (mA)	5000
Inrush Current (A)	60
Inrush Duration (µs)	300
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	6
Max. Luminaires per 13A C Breaker	8
Max. Luminaires per 16A C Breaker	9
Max. Luminaires per 20A C Breaker	10
Max. Luminaires per 10A B Breaker	3
Max. Luminaires per 13A B Breaker	4

## Start Highbay

START Highbay IP65 1-10V 26000lm 840 MB

0039346

Max. Luminaires per 16A B Breaker	5
Max. Luminaires per 20A B Breaker	7

### Lifetime data

Lumen maintenance - L70 B50	54000
Lumen maintenance - L70 B20	54000
Lumen maintenance - L70 B10	54000
Lumen maintenance - L80 B50	50000
Lumen maintenance - L80 B20	50000
Lumen maintenance - L80 B10	50000
Lumen maintenance - L90 B50	22000
Lumen maintenance - L90 B20	22000
Lumen maintenance - L90 B10	22000
Average life (Nominal) (h)	50000

### Physical data









Housing colour	Black
IP rating	IP65
IK rating	IK08
Diffuser finish	Clear
Diffuser material	Polycarbonate
Nominal Product Length (mm)	339
Nominal Product Width (mm)	339
Nominal Product Height (mm)	194
Weight (kg)	3.7

### Packaging

Single packaging type	Carton
Product EAN number	5410288393469
Packaging single length / height (cm)	40.0
Packaging single width (cm)	40.0
Packaging single depth (cm)	18.7
DUN14 (outer)	05410288393469
Units per outer package	1
Packaging outer length / height (cm)	40.0
Packaging outer width (cm)	40.0
Packaging outer depth (cm)	18.7

## PHOTOMETRY


## Start Highbay START Highbay IP65 1-10V 26000lm 840 MB 0039346




## Start Highbay


START Highbay IP65 1-10V 26000lm 840 MB  
0039346

### TECHNICAL DRAWINGS




**SYLVANIA** 0039346

 This luminaire contains built in LED lamps.




The lamps cannot be changed in the luminaire.

874/2012 


## Start Highbay

START Highbay IP65 1-10V 26000lm 840 MB  
0039346




This luminaire contains built in LED lamps.

The lamps cannot be changed in the luminaire.



**LED**



**SYLVANIA** 0039346 874/2012