

Product datasheet

Specifications



standard Network Interface Module STB - Ethernet modbus TCP/IP - 10...100 Mbits

STBNIP2311

Main

Range Of Product	Modicon STB distributed I/O solution
Product Or Component Type	Standard Network Interface Module
Integrated Connection Type	Ethernet Modbus TCP/IP conforming to IEEE 802.3 2 female RJ45 double shielded twisted pair via Ethernet (network) Ethernet Modbus TCP/IP conforming to IEEE 802.3 HE-13 (RS232 port) Ethernet Modbus TCP/IP conforming to IEEE 802.3 8-way female (RS232 port)
Port Ethernet	10BASE-T/100BASE-T
Exchange Mode	Half or full duplex
Number Of Segments	1 primary, maximum 6 extensions
Transmission Rate	10/100 Mbit/s for bus length of 0...100 m per segment
Structure Type	Industrial LAN Ethernet Modbus TCP/IP network

Complementary

Number Of Addressable I/O Module	0...32 per island
Communication Service	SNMP agent BootP/DHCP protocol Modbus TCP/IP messaging Embedded web (configuration,diagnostics and access to variable)
[Us] Rated Supply Voltage	24 V DC
Power Supply Type	SELV
Maximum Supply Current	700 A
Supply Voltage Limits	19.2...30 V
Input Current	550 mA for supply circuit
Nominal Output Current	0.575 A at 60...70 °C 1.2 A
Output Voltage	5.25 V DC (tolerance: +/- 0.21 %) for logic bus
Marking	CE
Overtoltage Category	II
Status Led	1 LED ACT 1 LED island state (RUN) 1 LED module error (ERR) 1 LED MS 1 LED NS 1 LED power supply (PWR) 1 LED test mode (TEST)
Depth	70 mm
Height	40.5 mm

Width	130 mm
Net Weight	0.145 kg

Environment

Standards	IEC 61131-2 : 2003 FM Class 1 division 2, groups A, B, C and D T4A with 70 °C
Product Certifications	UL ODVA C-Tick ATEX Cat 3G CSA
Pollution Degree	2 conforming to IEC 60664-1
Operating Altitude	<= 2000 m
Ip Degree Of Protection	IP20 conforming to IEC 61131-2 class 1
Ambient Air Temperature For Operation	0...60 °C (without derating) -25...70 °C (with derating factor)
Ambient Air Temperature For Storage	-40...85 °C
Relative Humidity	95 % at 60 °C without condensation
Vibration Resistance	3 gn at 58...150 Hz on 35 x 7.5 mm symmetrical DIN rail 5 gn at 58...150 Hz on 35 x 15 mm symmetrical DIN rail +/-0.35 mm at 10...58 Hz
Shock Resistance	30 gn for 11 ms conforming to IEC 88 reference 2-27

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.300 cm
Package 1 Width	7.300 cm
Package 1 Length	13.000 cm
Package 1 Weight	171.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	30
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	5.450 kg

Contractual warranty

Warranty	18 months
-----------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Dimensions Drawings

Dimensions

