

SUBMARINE
Submarine
Flood Light Series

- Streamline design for heat-dissipation and water run-off
- Stealth black tactile color choice for various outdoor use scenarios
- Patented anti-siphon design (IP66)
- Fortified tempered glass strengthens product quality
- Samsung LED chip enables high lumen efficacy

2023
New
Product



10000lm
100W



RISK 0
 3000K 4000K 6500K
 50/60Hz
 30000hrs
 220-240V 100-240V
 IP66
 IK06
 -20°C~40°C
 Flicker free

 L, W, H

 CRI ≥80



Item Number	Watts(W)	P.F.	Luminous Flux(lm)	Beam angle(°)
UFL/FX/0/1/0/SQ	10W	0.5/0.9	1000lm	120°

Dimension: 105mmx80x26mm



Item Number	Watts(W)	P.F.	Luminous Flux(lm)	Beam angle(°)
UFL/FX/0/1/0/SQ	20W	0.5/0.9	2000lm	120°

Dimension: 139mmx96x26mm



Item Number	Watts(W)	P.F.	Luminous Flux(lm)	Beam angle(°)
UFL/FX/0/1/0/SQ	30W	0.5/0.9	3000lm	120°

Dimension: 188mmx133x30mm



Item Number	Watts(W)	P.F.	Luminous Flux(lm)	Beam angle(°)
UFL/FX/0/1/0/SQ	50W	0.5/0.9	5000lm	120°

Dimension: 224mmx160x32mm



Item Number	Watts(W)	P.F.	Luminous Flux(lm)	Beam angle(°)
UFL/FX/0/1/0/SQ	70W	0.5/0.9	7000lm	120°
UFL/FX/0/1/0/SQ	100W	0.5/0.9	10000lm	120°

Dimension: 328mmx225x34mm



Item Number	Watts(W)	P.F.	Luminous Flux(lm)	Beam angle(°)
UFL/FX/0/1/0/SQ	150W	0.5/0.9	15000lm	120°

Dimension: 382mmx288x36mm



Item Number	Watts(W)	P.F.	Luminous Flux(lm)	Beam angle(°)
UFL/FX/0/1/0/SQ	200W	0.5/0.9	20000lm	120°

Dimension: 449mmx330x36mm