



### Main

Range	ZENcelo
Product or component type	Key card switch
Rated current	16 A at 240 V AC
Colour tint	Wine gold

### Complementary

Device mounting	Flush Surface
Connections - terminals	Brass terminal
Clamping connection capacity	3 x 4 mm <sup>2</sup> for solid cable(s) 3 x 4 mm <sup>2</sup> for stranded cable(s) 2 x 2.5 mm <sup>2</sup> for solid cable(s) 2 x 2.5 mm <sup>2</sup> for stranded cable(s)
Embedding depth	29.1 mm
Width	87.2 mm
Height	87.2 mm
Depth	41.1 mm

### Environment

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Ambient air temperature for storage	0...60 °C
Standards	GB 16915.2 IEC 60669-2-1

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>