

## Parallel Connected Capacitors with Break-action Mechanism

### Capacitors type B

Ref. No.	Capacity μF	Temperature range °C	Drawing	Ø (D) mm	Length (L) mm	Male nipple/ length (mm)	Weight g	Unit pcs.
<b>250 V, 50/60 Hz</b>								
<b>536378</b>	2.0	-40 to 100	A	25	63	M8x10	85	100
<b>536379</b>	4.0	-40 to 100	A	25	63	M8x10	80	100
<b>536380</b>	6.0	-40 to 100	A	25	63	M8x10	80	100
<b>536381</b>	8.0	-40 to 100	A	25	63	M8x10	85	100
<b>551645</b>	9.0	-40 to 100	A	30	78	M8x10	95	100
<b>536382</b>	10.0	-40 to 100	A	30	78	M8x10	90	100
<b>536383</b>	12.0	-40 to 100	A	30	78	M8x10	90	100
<b>536384</b>	13.0	-40 to 100	A	30	78	M8x10	90	100
<b>536385</b>	16.0	-40 to 100	A	35	78	M8x10	90	81
<b>536386</b>	18.0	-40 to 100	A	35	78	M8x10	90	81
<b>536387</b>	20.0	-40 to 100	A	35	78	M8x10	90	81
<b>536388</b>	25.0	-40 to 100	A	40	78	M8x10	100	64
<b>536389</b>	30.0	-40 to 100	A	35	103	M8x10	100	81
<b>536390</b>	32.0	-40 to 100	A	35	103	M8x10	120	81
<b>536391</b>	35.0	-40 to 100	A	40	103	M8x10	120	64
<b>536392</b>	40.0	-40 to 100	A	40	103	M8x10	120	64
<b>536393</b>	45.0	-40 to 100	A	40	103	M8x10	150	64
<b>536394</b>	50.0	-40 to 100	A	45	103	M8x10	150	49
<b>536395</b>	55.0	-40 to 100	A	45	103	M8x10	150	49
<b>536396</b>	60.0	-40 to 100	A	45	103	M8x10	200	49
<b>380-450 V, 50/60 Hz</b>								
<b>536397</b>	13.0	-40 to 85	A	35	103	M8x10	100	81
<b>536398</b>	18.0	-40 to 85	A	40	103	M8x10	120	64
<b>536399</b>	28.0	-40 to 85	A	45	103	M8x10	150	49
<b>536400</b>	32.0	-40 to 85	A	45	103	M8x10	200	49
<b>536401</b>	37.0	-40 to 85	A	50	103	M12x12	200	36
<b>536402</b>	50.0	-40 to 85	A	55	103	M12x12	250	36
<b>536403</b>	55.0	-40 to 85	B	50	128	M12x12	250	36
<b>536404</b>	60.0	-40 to 85	B	55	128	M12x12	250	36
<b>536405</b>	85.0	-40 to 85	B	60	138	M12x12	300	36

1

2

3

4

5

6

7

8

9

10