



Main

| | |
|---------------------------|---------------------------|
| Range | Vivace |
| Product or component type | Socket-outlet with switch |
| Device short name | KB113 |
| Device application | Power supply Control |
| Device presentation | Complete mechanism |

Complementary

| | |
|----------------------------|---|
| Pilot light | Red neon indicator |
| Outlet poles configuration | 2P + E |
| Number of gangs | 1 gang |
| Colour tint | White |
| Material | Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base |
| Projecting depth | 8 mm |
| Device mounting | Flush |
| Mounting support | Wall mounted |
| Fixing mode | By screw M3.5 |
| Fixing center | 60.3 mm |
| Embedding depth | 35 mm |
| Rated current | 13 A at 250 V AC, no inductive load |
| Network frequency | 50 Hz |
| Contacts material | Brass and phosphor bronze |
| Connections - terminals | Pillar terminal |
| Terminal identifier | L Earth N |
| Tightening torque | 0.4 N.m |

| | |
|------------------------------|--|
| Clamping connection capacity | 3 x 2.5 mm ² 2 x 4 mm ² |
| Width | 86 mm |
| Height | 86 mm |

Environment

| | |
|---------------------------------------|------------|
| Standards | IEC 60884 |
| Ambient air temperature for operation | -5...40 °C |
| Relative humidity | 0...95 % |
| Environmental characteristic | Indoor use |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Green Premium product |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |