



Main

| | |
|---------------------------|---------------------------|
| Range | Vivace |
| Product or component type | Socket-outlet with switch |
| Device short name | KB15 |
| Device application | Power supply |
| Device presentation | Complete mechanism |

Complementary

| | |
|------------------------------|---|
| Pilot light | Red neon indicator |
| Outlet poles configuration | 2P + E |
| Number of gangs | 1 gang |
| Colour tint | White |
| Material | Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base |
| Projecting depth | 8 mm |
| Device mounting | Flush |
| Mounting support | Wall mounted |
| Fixing mode | By screw M3.5 |
| Fixing center | 60.3 mm |
| Embedding depth | 35 mm |
| Rated current | 13 A at 250 V AC, no inductive load |
| Network frequency | 50 Hz |
| Contacts material | Brass and phosphor bronze |
| Connections - terminals | Pillar terminal |
| Terminal identifier | N Earth L |
| Tightening torque | 0.4 N.m |
| Clamping connection capacity | 2 x 4 mm ² 3 x 2.5 mm ² |
| Width | 86 mm |
| Height | 86 mm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

| | |
|---------------------------------------|-------------------------------|
| Standards | BS 1362-2 SS 145 MS 589 |
| Ambient air temperature for operation | -5...40 °C |
| Relative humidity | 0...95 % |
| Environmental characteristic | Indoor use |

Offer Sustainability

| | |
|--------------------------|---|
| EU RoHS Directive | Under investigation |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |