



Main

Range	Vivace
Product or component type	Socket-outlet with switch
Device short name	KB15
Device application	Power supply Control
Device presentation	Complete mechanism

Complementary

Pilot light	Red neon indicator
Outlet poles configuration	2P + E
Number of gangs	1 gang
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Rated current	13 A at 250 V AC, resistive
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	L N Earth
Tightening torque	0.4 N.m
Clamping connection capacity	2 x 4 mm ² 3 x 2.5 mm ²
Width	87 mm
Height	87 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Standards	SS 145 MS 589 BS 1363
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Operating altitude	<= 2000 m
Environmental characteristic	Indoor use