



### Main

|                           |                           |
|---------------------------|---------------------------|
| Range                     | Vivace                    |
| Product or component type | Socket-outlet with switch |
| Device short name         | KB25                      |
| Device application        | Power supply              |
| Device presentation       | Complete mechanism        |

### Complementary

|                              |   |
|------------------------------|---|
| Outlet poles configuration   | 2P + E  |
| Number of gangs              | 2 gangs   |
| Colour tint                  | Aluminium silver  |
| Material                     | Polycarbonate: grid plate<br>Polycarbonate: surround<br>Polycarbonate: base |
| Projecting depth             | 8 mm  |
| Device mounting              | Flush   |
| Mounting support             | Wall mounted  |
| Fixing mode                  | By screw M3.5   |
| Fixing center                | 120.6 mm  |
| Embedding depth              | 35 mm   |
| Rated current                | 13 A at 250 V AC, resistive   |
| Network frequency            | 50 Hz   |
| Contacts material            | Brass and phosphor bronze   |
| Connections - terminals      | Pillar terminal   |
| Terminal identifier          | L<br>N<br>Earth   |
| Tightening torque            | 0.4 N.m   |
| Clamping connection capacity | 3 x 2.5 mm <sup>2</sup><br>2 x 4 mm <sup>2</sup>                            |
| Width                        | 147 mm  |
| Height                       | 87 mm   |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

|                                       |                               |
|---------------------------------------|-------------------------------|
| Standards                             | SS 145<br>MS 589<br>BS 1362-2 |
| Ambient air temperature for operation | -5...40 °C                    |
| Relative humidity                     | 0...95 %                      |
| Environmental characteristic          | Indoor use                    |

## Offer Sustainability

|                          |   |
|--------------------------|---|
| EU RoHS Directive        | Under investigation                           |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a> |