



### Main

|                           |                           |
|---------------------------|---------------------------|
| Range                     | Vivace                    |
| Product or component type | Socket-outlet with switch |
| Device short name         | KB25                      |
| Device application        | Power supply<br>Control   |
| Device presentation       | Complete mechanism        |

### Complementary

|                              |   |
|------------------------------|---|
| Outlet poles configuration   | 2P + E  |
| Number of gangs              | 2 gangs   |
| Colour tint                  | White   |
| Material                     | Polycarbonate: grid plate<br>Polycarbonate: surround<br>Polycarbonate: base |
| Projecting depth             | 8 mm  |
| Device mounting              | Flush   |
| Mounting support             | Wall mounted  |
| Fixing mode                  | By screw M3.5   |
| Fixing center                | 120.6 mm  |
| Embedding depth              | 35 mm   |
| Rated current                | 13 A at 250 V AC, resistive   |
| Network frequency            | 50 Hz   |
| Contacts material            | Brass and phosphor bronze   |
| Connections - terminals      | Pillar terminal   |
| Terminal identifier          | Earth<br>L<br>N   |
| Tightening torque            | 0.4 N.m   |
| Clamping connection capacity | 3 x 2.5 mm <sup>2</sup>   |

|        |                       |
|--------|-----------------------|
|        | 2 x 4 mm <sup>2</sup> |
| Width  | 147 mm                |
| Height | 87 mm                 |

## Environment

|                                       |                               |
|---------------------------------------|-------------------------------|
| Standards                             | MS 589<br>BS 1362-2<br>SS 145 |
| Ambient air temperature for operation | -5...40 °C                    |
| Relative humidity                     | 0...95 %                      |
| Environmental characteristic          | Indoor use                    |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | No need of specific recycling operations  |